

G Series - Extended Momentary Contact Single Push Button Operator - Red Button With "Reset"/Blank Nameplate - 1NO/1NC Contact Rating

By Killark

Catalog # [GOL1R3](#)

G Series - Aluminum Extended Momentary Contact Single Push Button Operator - Red Button With "Reset"/Blank Nameplate - 1NO/1NC Contact Rating.



*Representative Image

Features

- Operators are all aluminum except for certain movable parts which are stainless steel.
- All other parts such as screws are either stainless steel or plated steel.
- Threaded bodies are all $\frac{3}{4}$ "-14 NPSM thread.
- Control stations can be grouped into a single assembly thus reducing installation time and cost.

General

Action	Momentary
Actuator	Single Pushbutton
Ambient Temp. Range	UL: -25 to 40 °C, CSA: -50 to 40 °C, IEC: -20 to 40 °C
Application	
Catalog Number	GOL1R3
EU RoHS Indicator	Contact Manufacturer
Number Of Poles	1
Series	GO
Type	
UPC	783936226057

Dimensions

Dimensions	6.31 in x 2.25 in x 1.25 in
Gross Weight with Packaging	0.5
Height	1.25 in
Length	6.31 in
Width	2.25 in

Electrical Ratings

Amperage Rating	10 A
Contact Rating	60A INRUSH @ 120 VAC; 30A INRUSH @ 240 VAC; 15A INRUSH @ 480 VAC; 12A INRUSH @ 600 VAC; 0.55A INRUSH @ 125 VDC; 0.275A INRUSH @ 250 VDC; 6A BREAKING @ 120 VAC; 3A BREAKING @ 240 VAC; 1.5A BREAKING @ 480 VAC; 1.2A BREAKING @ 600 VAC; 0.55A BREAKING @ 125 VDC; 0.275A BREAKING @ 250 VDC; 10A CARRYING @ 120 VAC; 10A CARRYING @ 240 VAC; 10A CARRYING @ 480 VAC; 10A CARRYING @ 600 VAC; 2.5A CARRYING @ 125 VDC; 2.5A CARRYING @ 250 VDC.
Frequency Rating	50/60 Hz

Certifications And Compliance

CSA File Number	LR11714
Hazardous Rating(s)	Class I, Divisions 1 & 2, Groups B, C, D
	Class I, Zones 1 & 2, Groups IIB, IIA
	Class II, Divisions 1 & 2, Groups E, F, G
	Class III, Divisions 1 & 2
Nema Rating	3, 4, 4X
UL File Number	E12379

Product Assets

[Certifications - GO Series Operators CSA Certificate of Compliance](#)

[Certifications - G Series Auxiliary Devices UL Certification](#)

[Customer Notices - Prop 65 Notice](#)

[Installation Manuals - GO1 & GOL1 Single Pushbutton Operators](#)

[IOM K1001](#)



A Hubbell brand

©2024 Hubbell Incorporated. All rights reserved
KILL_CA-GOL1R3-SPEC-EN | REV 6/2024