



G Series -Extended 120V Pilot Light Operator - Red Lens With Blank Nameplate

By Killark
Catalog # [GOL3R](#)

G Series - Aluminum Extended 120V Pilot Light Operator - Red
Lens With Blank Nameplate



Features

- Operators are all aluminum except for certain movable parts which are stainless steel.
- All other parts such as screws are either stainless steel or plated steel.
- Threaded bodies are all 3/4"-14 NPSM thread.
- Control stations can be grouped into a single assembly thus reducing installation time and cost.

Application

G Series custom control panel operators are designed for use in hazardous locations when installed in suitable enclosures such as B7E, EXB, XJB, DB, SWB, and GCS Series boxes and B7, Y7 starter enclosures.

Specifications

Nema Rating	3, 4, 4X
UL File Number	E12379
Buy America(n) Qualified	Contact Manufacturer
CSA File Number	LR11714
Hazardous Rating(s)	• Class I, Divisions 1 & 2, Groups B, C, D • Class I, Zones 1 & 2, Groups IIB, IIA • Class II, Divisions 1 & 2, Groups E, F, G • Class III, Divisions 1 & 2

Current

Frequency Rating	50/60 Hz
Amperage Rating	0.025 A
Voltage Rating	250 V

Dimensions

Height	1.875 in
Width	2.375 in
Length	6.625 in
Gross Weight with Packaging	0.4
Depth	3-3/8 in
Dimensions	6.625 in x 2.375 in x 1.875 in

General

Color	Red
Product Family	Controls
UPC	783936226217
Type	Indicator
Series	GO Series

Operational

Operating Cycles	10,000 hrs
Actuator	Pilot Light

Product Assets

[Catalog \[English\]](#)