



GZ Series 3 Position 1 Pole Momentary Left Selector Switch - Long Length 40mm, 3/4 NPSM

By Killark
Catalog # [GZ15-6](#)



3 Position 1 Pole Momentary Left Selector Switch - Long Length
40mm, 3/4 NPSM.

Features

- Operators are all aluminum except for certain movable parts which are stainless steel.
- All other parts such as screws are either stainless steel or plated steel.
- Threaded bodies are all 3/4"-14 NPSM thread and M22x1.5 on request.
- Control operators can be grouped into a single assembly thus reducing installation time and cost.

General

Action	Rotary
Catalog Number	GZ15-6
Color	Black
EU RoHS Indicator	Contact Manufacturer
Number Of Poles	1
Series	GZ
UPC	783936177052

Dimensions

Dimensions	4.5 in x 1.8 in x 1.8 in
Height	1.8 in
Length	4.5 in
Weight	0.4 lb
Width	1.8 in

Electrical Ratings

Amperage Rating	20 A
Frequency Rating	50/60 Hz

Certifications And Compliance

ATEX File Number	SIRA 19ATEX 1171 U
Hazardous Rating(s)	• Class I, Divisions 1 & 2, Groups B, C, D • Class II, Divisions 1 & 2, Groups E, F, G • Class III, Divisions 1 & 2 • Zones 1 & 2 • Zones 21 & 22 • II 2 G Ex db IIC/IIB+H2Gb • II 2 D Ex tb IIIC Db
IECEx File Number	IECEx SIR 19.0054 U
Nema Rating	Type 4X
UL File Number	E12379

Product Assets

- [Certifications - GZ Series IECEx Certificate](#)
- [Certifications - GZ Series Attestation of Conformity](#)
- [Certifications - GZ Series ATEX Certificate](#)
- [Certifications - GZ Series UL Certificate](#)
- [Engineering Drawing - GZ Series Dimensional Drawings](#)
- [Installation Manuals - GZ Series Actuators & Signal Devices](#)
- [Installation Manual K1506](#)
- [Sales Drawings - GZ Series Dimensional Drawings](#)
- [Specifications - GZ15-6 Specification Sheet French](#)
- [Specifications - GZ15-6](#)
- [Specifications - GO Series To GZ Series Cross Reference](#)
- [Specifications - GZ Series Operators Specification Sheet](#)
- [Video - GZ Operators](#)