# **KILLARK®**

# GZ Series Push Button Assembly BLACK w/ 1 N.O./1 N.C. Contact -Long Length 40mm, 3/4 NPSM

By Killark Catalog # GZ1-KX3

Push Button Assembly BLACK w/ 1 N.O./1 N.C. Contact - Long Length 40mm,  $\frac{3}{4}$  NPSM.



\*Representative Image

#### **Features**

- Operators are all aluminum except for certain movable parts which are stainless steel.
- All other parts such as screws are either stainless steel or plated steel.
- Threaded bodies are all  $\frac{3}{4}$ "-14 NPSM thread and M22x1.5 on request.
- Control operators can be grouped into a single assembly thus reducing installation time and cost.

#### General

Action Momentary
Color • Black
• Noir

EU RoHS Indicator Contact Manufacturer

Number Of Poles 2 Series GZ

Type • Push Button

• Push Button

UPC 783936175614

## **Dimensions**

Dimensions  $6.7 \text{ in } \times 1.8 \text{ in } \times 1.8 \text{ in}$ 

Height 1.8 in
Length 6.7 in
Weight 0.35 lb
Width 1.8 in

# **Electrical Ratings**

Amperage Rating 10 A Frequency Rating 50/60 Hz

### **Certifications and Compliance**

ATEX File Number SIRA 19ATEX 1171 U

Hazardous Rating(s)

• Class I, Divisions 1 & 2,
Groups B, C, D

• Class II, Divisions 1 & 2, Groups E, F, G

• Class III, Divisions 1 & 2

Zones 1 & 2Zones 21 & 22

• II 2 G Ex db IIC/IIB+H2Gb

• II 2 D Ex tb IIIC Db

IECEx File Number IECEx SIR 19.0054 U

Nema Rating Type 4X UL File Number E12379

### **Product Assets**

3D Models - GZ1-KX3 3D File (.STP)

Certifications - GZ Series ATEX Certificate

Certifications - GZ Series Attesation of Conformity

Certifications - GZ Series UL Certificate Certifications - GZ Series IECEx Certificate

Engineering Drawing - GZ Series Dimensional Drawings (DWG)

Installation Manuals - GZ Series Contact Block Stacking IOM k1515

Installation Manuals - GZ Series Actuators & Signal Devices Installation Manual K1506

Sales Drawings - GZ Series Dimensional Drawings (PDF)

Video - GZ Operators

