



GZ Series - PilotLight, Green with Lamp Holder & Lamp 120V AC/DC - Normal Length 25mm, 3/4 NPSM

By Killark
Catalog # [GZ23-G23](#)

Pilot Light, Green with Lamp Holder & Lamp 120V AC/DC - Normal Length 25mm, 3/4 NPSM.



Features

- Operators are all aluminum except for certain movable parts which are stainless steel.
- All other parts such as screws are either stainless steel or plated steel.
- Threaded bodies are all 3/4"-14 NPSM thread and M22x1.5 on request.
- Control operators can be grouped into a single assembly thus reducing installation time and cost.

General

Color	<ul style="list-style-type: none">• Green• Vert
EU RoHS Indicator	Contact Manufacturer
Series	GZ
Type	<ul style="list-style-type: none">• Pilot Light• Pilot Light
UPC	783936175652

Dimensions

Dimensions	4.2 in x 1.8 in x 1.8 in
Height	1.8 in
Length	4.2 in
Weight	0.20 lb
Width	1.8 in

Electrical Ratings

Amperage Rating	12 mA
Frequency Rating	50/60 Hz
Wattage	1.5 W

Certifications and Compliance

ATEX File Number	SIRA 19ATEX 1171 U
Hazardous Rating(s)	<ul style="list-style-type: none">• Class I, Divisions 1 & 2, Groups B, C, D• Class II, Divisions 1 & 2, Groups E, F, G• Class III, Divisions 1 & 2• Zones 1 & 2• Zones 21 & 22• II 2 G Ex db IIC/IIB+H2Gb• II 2 D Ex tb IIIC Db
IECEX File Number	IECEX SIR 19.0054 U
Nema Rating	Type 4X
UL File Number	E12379

Product Assets

- [3D Models - GZ23-G23 3D File \(.STP\)](#)
- [Certifications - GZ Series ATEX Certificate](#)
- [Certifications - GZ Series Attestation of Conformity](#)
- [Certifications - GZ Series UL Certificate](#)
- [Certifications - GZ Series IECEX Certificate](#)
- [Engineering Drawing - GZ Series Dimensional Drawings \(DWG\)](#)
- [Installation Manuals - GZ Series Actuators & Signal Devices](#)
- [Installation Manual K1506](#)
- [Sales Drawings - GZ Series Dimensional Drawings \(PDF\)](#)
- [Video - GZ Operators](#)



A proud member of the Hubbell Family.