KILLARK®

GZ Series - PilotLight, Red with Lamp Holder & Lamp 24V AC/DC - Long Length 40mm, 3/4 NPSM



By Killark
Catalog # GZB3-R4

Pilot Light, Red with Lamp Holder & Lamp 24V AC/DC - Long Length 40mm, 3/4 NPSM

Features

- Operators are all aluminum except for certain movable parts which are stainless steel.
- All other parts such as screws are either stainless steel or plated steel.
- Threaded bodies are all 3/4"-14 NPSM thread and M22x1.5 on request.
- Control operators can be grouped into a single assembly thus reducing installation time and cost.

Specifications

Nema Rating	Type 4X
UL File Number	E12379
ATEX File Number	SIRA 19ATEX 1171 U
IECEx File Number	IECEx SIR 19.0054 U
Hazardous Rating(s)	• Class I, Divisions 1 & 2, Groups B, C, D • Class II, Divisions 1 & 2, Groups E, F, G • Class III, Divisions 1 & 2 • Zones 1 & 2 • Zones 21 & 22 • II 2 G Ex db IIC/IIB+H2Gb • II 2 D Ex tb IIIC Db
EU RoHS Indicator	Contact Manufacturer

Current

Frequency Rating	50/60 Hz
Amperage Rating	12 mA
Wattage	1.5 W

Dimensions

Weight	0.25 lb.
Height	1.8 in
Width	1.8 in
Length	4.2 in
Dimensions	4.2 in x 1.8 in x 1.8 in

General

Color	Red
UPC	783936175843
Type	Pilot Light
Series	GZ Series

Product Assets

Installation Manual [English]

© 2026 Hubbell Incorporated. All rights reserved