KILLARK®

GZ Series - PilotLight, Amber with Lamp Holder & Lamp 24V AC/DC -Long Length 40mm, 3/4 NPSM

By Killark Catalog # GZB3-A4

Pilot Light, Amber with Lamp Holder & Lamp 24V AC/DC - Long Length 40mm, $\frac{3}{4}$ NPSM.



Features

- Operators are all aluminum except for certain movable parts which are stainless steel.
- All other parts such as screws are either stainless steel or plated steel.
- Threaded bodies are all ¾"-14 NPSM thread and M22x1.5 on request.
- Control operators can be grouped into a single assembly thus reducing installation time and cost.

General

Color • Amber • Amber

EU RoHS Indicator Contact Manufacturer

Series GZ

Type

Pilot Light
Pilot Light

UPC 783936175874

Dimensions

Dimensions 4.2 in \times 1.8 in \times 1.8 in

Height 1.8 in
Length 4.2 in
Weight 0.25 lb
Width 1.8 in

Electrical Ratings

Amperage Rating 12 mA
Frequency Rating 50/60 Hz
Wattage 1.5 W

Certifications and Compliance

ATEX File Number Hazardous Rating(s) SIRA 19ATEX 1171 U
• Class I, Divisions 1 & 2,
Groups B, C, D

• Class II, Divisions 1 & 2, Groups E. F. G

• Class III, Divisions 1 & 2

Zones 1 & 2Zones 21 & 22

• II 2 G Ex db IIC/IIB+H2Gb

• II 2 D Ex tb IIIC Db

IECEx File Number IECEx SIR 19.0054 U
Nema Rating Type 4X
UL File Number E12379

Product Assets

3D Models - GZB3-A4 3D File (.STP)

 ${\sf Certifications} \hbox{ - GZ Series ATEX Certificate}$

Certifications - GZ Series Attesation of Conformity

Certifications - GZ Series UL Certificate Certifications - GZ Series IECEx Certificate

Engineering Drawing - GZ Series Dimensional Drawings (DWG)

Installation Manuals - GZ Series Actuators & Signal Devices Installation Manual K1506

Sales Drawings - GZ Series Dimensional Drawings (PDF)

Video - GZ Operators

