



GZ Series Push Button Assembly
BLACK w/ 1 N.O./1 N.C. Contact -
Extra Long Length 57mm, 3/4
NPSM

By Killark
Catalog # [GZL1K3](#)



*Representative Image

Features

- Operators are all aluminum except for certain movable parts which are stainless steel.
- All other parts such as screws are either stainless steel or plated steel.
- Threaded bodies are all 3/4"-14 NPSM thread and M22x1.5 on request.
- Control operators can be grouped into a single assembly thus reducing installation time and cost.

General

Action	Momentary
Catalog Number	GZL1K3
Color	Black
	Noir
EU RoHS Indicator	Contact Manufacturer
Number Of Poles	2
Series	GZ
Type	
UPC	783936175645

Dimensions

Dimensions	6.7 in x 1.8 in x 1.8 in
Height	1.8 in
Length	6.7 in
Weight	0.45 lb
Width	1.8 in

Electrical Ratings

Amperage Rating	10 A
Frequency Rating	50/60 Hz

Certifications And Compliance

ATEX File Number	SIRA 19ATEX 1171 U
Hazardous Rating(s)	Class I, Divisions 1 & 2, Groups B, C, D
	Class II, Divisions 1 & 2, Groups E, F, G
	Class III, Divisions 1 & 2
	Zones 1 & 2
	Zones 21 & 22
	II 2 G Ex db IIC/IIB+H2Gb
	II 2 D Ex tb IIIC Db
IECEx File Number	IECEx SIR 19.0054 U
Nema Rating	Type 4X
UL File Number	E12379

Product Assets

- [3D Models - GZL1K3 3D File](#)
- [Certifications - GZ Series ATEX Certificate](#)
- [Certifications - GZ Series IECEx Certificate](#)
- [Certifications - GZ Series Attestation of Conformity](#)
- [Certifications - GZ Series UL Certificate](#)
- [Engineering Drawing - GZ Series Dimensional Drawings](#)
- [Installation Manuals - GZ Series Contact Block Stacking IOM K1515](#)
- [Installation Manuals - GZ Series Actuators & Signal Devices](#)
- [Installation Manual K1506](#)
- [Sales Drawings - GZ Series Dimensional Drawings](#)
- [Video - GZ Operators](#)



A Hubbell brand

©2024 Hubbell Incorporated. All rights reserved
KILL_CA-GZL1K3-SPEC-EN | REV 6/2024