KILLARK®

GZ Series Push Button Assembly Red w/ 1 N.O./1 N.C. Contact - Extra Long Length 57mm, 3/4 NPSM

By Killark
Catalog # GZL1R3

Push Button Assembly Red w/ 1 N.O./1 N.C. Contact - Extra Long Length 57mm, 3/4 NPSM.

*Representative Image

Features

- Operators are all aluminum except for certain movable parts which are stainless steel.
- All other parts such as screws are either stainless steel or plated steel.
- Threaded bodies are all ¾"-14 NPSM thread and M22x1.5 on request.
- Control operators can be grouped into a single assembly thus reducing installation time and cost.

General

Action	Momentary
Catalog Number	GZL1R3
Color	Red
EU RoHS Indicator	Contact Manufacturer
Number Of Poles	2
Series	GZ
UPC	783936175621

Dimensions

Dimensions	6.7 in x 1.8 in x 1.8 in
Height	1.8 in
Length	6.7 in
Weight	0.45 lb
Width	1.8 in

Electrical Ratings

Amperage Rating	10 A
Frequency Rating	50/60 Hz

Certifications And Compliance

ATEX File Number	SIRA 19ATEX 1171 U
Hazardous Rating(s)	• Class I, Divisions 1 & 2, Groups B, C, D
	• Class II, Divisions 1 & 2, Groups E, F, G
	• Class III, Divisions 1 & 2
	• Zones 1 & 2
	• Zones 21 & 22
	• II 2 G Ex db IIC/IIB+H2Gb
	• II 2 D Ex tb IIIC Db
IECEx File Number	IECEx SIR 19.0054 U
Nema Rating	Type 4X
UL File Number	E12379

Product Assets

3D Models - GZL1R3 3D File
Certifications - GZ Series IECEx Certificate
Certifications - GZ Series Attesation of Conformity
Certifications - GZ Series ATEX Certificate
Certifications - GZ Series UL Certificate
Engineering Drawing - GZ Series Dimensional Drawings
Installation Manuals - GZ Series Actuators & Signal Devices Installation Manual K1506
Installation Manuals - GZ Series Contact Block Stacking IOM K1515
Sales Drawings - GZ Series Dimensional Drawings
Specifications - GZL1R3 Specification Sheet French
Specifications - GO Series To GZ Series Cross Reference
Specifications - GZL1R3
Specifications - GZ Series Operators Specification Sheet
Video - GZ Operators