KILLARK®

GZ Series Mushroom Head Redwith Latch Actuator Twist Release w/ 1 N.O./1 N.C. - Long Length 40mm, 3/4 NPSM

By Killark Catalog # GZMT1-RM3



Features

- Operators are all aluminum except for certain movable parts which are stainless steel.
- All other parts such as screws are either stainless steel or plated steel.
- Threaded bodies are all %"-14 NPSM thread and M22x1.5 on request.
- Control operators can be grouped into a single assembly thus reducing installation time and cost.

General

Action Maintained
Catalog Number GZMT1-RM3
Color Red

EU RoHS Indicator Contact Manufacturer

Number Of Poles 2 Series GZ

UPC 783936176147

Dimensions

Dimensions 6.7 in x 1.8 in x 1.8 in

Height 1.8 in
Length 6.7 in
Weight 0.4 lb
Width 1.8 in

Electrical Ratings

Amperage Rating 10 A Frequency Rating 50/60 Hz

Certifications And Compliance



ATEX File Number Hazardous Rating(s) **SIRA 19ATEX 1171 U**

- Class I, Divisions 1 & 2,
 Groups B, C, D
- Class II, Divisions 1 & 2, Groups E, F, G
- Class III, Divisions 1 & 2
- Zones 1 & 2
- Zones 21 & 22
- II 2 G Ex db IIC/IIB+H2Gb
- II 2 D Ex tb IIIC Db

IECEx SIR 19.0054 U Type 4X E12379

IECEx File Number Nema Rating UL File Number

Product Assets

3D Models - GZMT1-RM3 3D File

Certifications - GZ Series IECEx Certificate

Certifications - GZ Series Attesation of Conformity

Certifications - GZ Series ATEX Certificate Certifications - GZ Series UL Certificate

Engineering Drawing - GZ Series Dimensional Drawings

Installation Manuals - GZ Series Actuators & Signal Devices

Installation Manual K1506

Installation Manuals - GZ Series Contact Block Stacking IOM

K1515

Sales Drawings - GZ Series Dimensional Drawings

Specifications - GZMT1-RM3 Specification Sheet French

Specifications - GO Series To GZ Series Cross Reference

Specifications - GZ Series Operators Specification Sheet

Specifications - GZMT1-RM3

Video - GZ Operators

