



HK Instrument Enclosure, 3-1/2 ID RD Body
3" DP & Lens Cover, Class I, II, III, BCDEFG,
UL/CSA/FM, Cast Aluminum, Type 4 IP66,

By Killark
Catalog # [HKB-GL](#)

HK Series, 3-1/2 ID RD Body 3" DP & Lens Cover, Class I, II, III,
BCDEFG, UL/CSA/FM, Cast Aluminum, Type 4 IP66, Instrument
Enclosure

Features

- Compact round body instrument enclosures with threaded glass lens screw covers provide easy access to interior.
- High strength, lighter weight, corrosion resistant copper free cast aluminum construction.
- Glass lens made of tempered soda lime.
- Cover o-ring, Nitrile (BUNA-N) material, supplied standard
- supplied standard for a Type 4X rating.
- Cast mounting lugs are standard on all boxes.
- Internal ground screw supplied on all boxes.
- Electrostatically applied gray powder epoxy/polyester finish on exterior of box and covers.
- Offset feed-thru conduit openings (3/4" NPT) for maximum use of interior volume.
- Interior "X"-configuration mounting pad for instrument/device cast into the bottom of the box provided for flexibility.
- Covers have shrouded tamper resistant set screws as standard.

Application

Instrumentation housed in HK Series enclosures typically used to measure, detect, monitor, transmit, and control industrial processes and systems. HK Series enclosures are suitable for a broad range of applications, meeting both domestic and international



Specifications

CSA File Number	LR11716
EU RoHS Indicator	Contact Manufacturer
UL File Number	E83696
Hazardous Rating(s)	• Class I, Divisions 1 & 2, Groups A(suffix GA) B, C, D • Class I, Zones 1 & 2, Groups IIB+H2, IIA • Class II, Divisions 1 & 2, Groups E, F, G • Class III, Divisions 1 & 2

Dimensions

Length	6.5 in
Height	5 in
Width	6.125 in
Gross Weight with Packaging	3.48
Dimensions	6.5 in x 6.125 in x 5 in

General

Color	Gray
Series	HK Series
UPC	783936295428
Type	Enclosure & Lens Cover
Material	Copper-free aluminum
Cover Type	Threaded