

K0501-G - 1/2 IN Straight Liquidtight Connector Insulated Grounding Lug

By Killark

Catalog # [K0501-G](#)

1/2 IN Straight Liquidtight Connector Insulated Grounding Lug.



*Representative Image

Features

- Lay-in grounding lug
- Plated steel for excellent durability
- Insulated throat fittings protect conductors from insulation damage

General

Catalog Number	K0501-G
Color	Gray
	Gris
EU RoHS Indicator	Contact Manufacturer
Finish Type	Plaqué zinc
Grounding Style	External Lug
Insulation Type	Insulated
Material	Steel
Series	K Series
Style	Straight
Type	
UPC	783936383514

Logistics

Carton Quantity 25

Product Assets

[Catalogs - Killark Catalog](#)

[Customer Notices - Prop 65 Notice](#)

Dimensions

Hub Size	1/2"
Weight	0.22 lb

Certifications And Compliance

CSA File Number	LR70873
Hazardous Rating(s)	Suitable for use in hazardous location applications when installed according to NEC Articles 501.10(B) (Class I, Division 2) or 502.10(A)(B) (Class II, Divisions 1 & 2) and 505.15(C) (Class I Zone 2).
UL File Number	E22699/E152165



A Hubbell brand

©2024 Hubbell Incorporated. All rights reserved
KILL_CA-K0501G-SPEC-EN | REV 6/2024