



KFL2033 - KFL-X 20000 LUMEN 347-480 VAC 50/60 Hz 5000K CCT 70 CRI

By Killark
Catalog # [KFL2033](#)

KFL-X 20000 LUMEN 347-480 VAC 50/60 Hz 5000K CCT 70 CRI



Features

-
-
-
-
-
-
-
-
-
-

General

Catalog Number	KFL2033
Color Temperature	5000 K
EU RoHS Indicator	Contact Manufacturer
Finish Type	Powder Epoxy Paint
Light Source	LED
Lumen Range	15,001-25,000 lm
Material	Aluminum, Copper Free (less than 4/10 of 1%)
Operating Temperature	-50°C to +55 °C
Optic Type	Glass Lens
Series	KFL-X
Type	Floodlight
UPC	783936186030

Dimensions

Hub Size	3/4 NPT or M25
----------	----------------

Electrical Ratings

Frequency Rating	50/60 Hz
Voltage Rating	347-480 VAC
Wattage	180 W

Product Assets

- [3D Models - KFL-X Series 3D Model](#)
- [3D Models - KFL-X Series With Dark Sky 3D Model](#)
- [3D Product View - KFL-X](#)
- [Brochures - KFL-X Brochure](#)
- [Certifications - KFLX Series UKCA Certification](#)
- [Certifications - KFLX Series UKCA UK Type Certification](#)
- [Certifications - KFL-X Series ATEX Certificate EU Type](#)
- [Certifications - KFL-X Series CSA Certificate](#)
- [Certifications - KFLX Series Attestation of Conformity](#)
- [Certifications - KFLX Series IEx Certificate of Conformity](#)
- [Certifications - KFL-X Series IECEx Certificate of Conformity](#)
- [Certifications - KFL-X Series ATEX Certificate](#)
- [Engineering Drawing - KFL-X Series With Dark Sky 2D Engineering Drawing](#)
- [Engineering Drawing - KFL-X Series 2D Engineering Drawing](#)
- [Installation Manuals - KFL-X Series IOM K1505](#)
- [Sales Drawings - KFL-X Series With Dark Sky Sales Drawing](#)
- [Sales Drawings - KFL-X Series Sales Drawing](#)
- [Specifications - KFL2033 Specification Sheet French](#)
- [Specifications - KFL-X Series Floodlights Specification Sheet](#)
- [Specifications - KFL2033 Specification Sheet English](#)
- [Video - KFL-X Product Video](#)
- [Video - KFL-X Product Video](#)