KILLARK®

KP Series 60 Amp Plug - D Type - 3P 4W Circuit - Grommet Range 0.500-0.875 Inch - 115/230VAC 60Hz



By Killark
Catalog # KP-604D345

KP Series - Aluminum 60 Amp Plug - D Type - 3W 4P Circuit - Grommet Range 0.500-0.875 Inch - 115/230VAC 60Hz

Features

- Suitable where a connection is required for portable or movable equipment such as tools, motors, hand lights, etc.
- Solder Terminations for sure connection
- Copper free aluminum housing
- Delayed action contacts ensure safe interconnect
- Wide range of grommet openings
- Extra long grounding pin makes contact first and breaks contact last

Specifications

Nema Rating	3, 4, 4X, 7(B, C, D), 9(F, G)
Hazardous Rating(s)	• Class I, Divisions 1 & 2, Groups C, D • Class I, Zones 1 & 2, Groups IIB,IIA
EU RoHS Indicator	Contact Manufacturer

Conductor

Number Of Poles	3
Number Of Wires	4

Current

Amperage Rating	60 A

Dimensions

Weight	2.5 lb.

General

UPC	783936370132
Type	Pin & Sleeve
Receptacle Type	Delayed Action
Material	Aluminum, Copper Free (less than 4/10 of 1%)
Series	KP Series

Logistics

Carton Quantity	5

Product Assets

Catalog [English]
Installation Manual [English]

© 2026 Hubbell Incorporated. All rights reserved