



LB67SA - 2" LB Hub, Aluminum Form 7 Conduit Body

By Killark
Catalog # [LB67SA](#)

2" LB Hub, Aluminum Form 7 Conduit Body



*Representative Image

Features

- Enhanced sealing capabilities neoprene sealing gaskets provide a NEMA 3 Seal.
- Suitable for wet locations when used with gaskets.
- High-quality sealing hardware 316 stainless steel cover screws and washers with neoprene gaskets.
- Innovative spring clip design for installation ease and repeat usage.
- For use with threaded rigid conduit steel or aluminum.
- Flat-back design for greater wiring capacity and mounting stability.

Application

- To provide access to conductors for pulling, splicing, and maintenance. Threaded for rigid conduit and IMC.

General

Catalog Number	LB67SA
Color	Gray
EU RoHS Indicator	Contact Manufacturer
Finish Type	Powder Epoxy Paint
Hub Pattern	LB
Material	Aluminum, Copper Free (less than 4/10 of 1%)
Series	Duraloy 7
Type	Conduit Body
UPC	783936080055

Dimensions

Dimensions	11.875 in x 7.375 in x 4.125 in
Gross Weight with Packaging	1.86
Height	4.125 in
Hub Size	2"
Length	11.875 in
Width	7.375 in

Certifications And Compliance

Buy America(n) Qualified	TAA Compliant (All status valid till December 2025)
CSA File Number	LR11852
Hazardous Rating(s)	Suitable for use in hazardous location applications when installed according to NEC Articles 501.10(b) (Class I, Division 2) or 502.10, 503.10, and 505.15 (Class I Zone 2).
UL File Number	E3397

Product Assets

- [Catalogs - Killark Catalog](#)
- [Certifications - Duraloy 7 UL Certificate of Compliance](#)
- [Customer Notices - Prop 65 Notice](#)
- [Installation Manuals - KIL_Duraloy 7 Series Conduit Bodies IOM_K1430](#)
- [Specifications - Duraloy 7 Series Conduit Bodies Specification Sheet](#)