

OLB-1

By Killark
Catalog # **OLB-1**

½" LB Hub O Series Conduit Body.



*Representative Image

Features

- Raintight when used with gasketed covers.
- Malleable iron suitable for use in concrete.
- Interchangeable with competitive products.
- Stainless steel screws on stamped and cast covers.
- Tapered threaded hubs (NPT).

Application

To provide access to conductors for pulling, splicing, and maintenance. Threaded for rigid conduit and IMC.

General

Color	<ul style="list-style-type: none">• Gray• Gris
Finish Type	Peinture époxy en poudre
Hub Pattern	LB
Material	Aluminum, Copper Free (less than 4/10 of 1%)
Series	O Series
Type	<ul style="list-style-type: none">• Conduit Body• Conduit Body
UPC	783936490250

Dimensions

Dimensions	5 in x 2 in x 3 in
Gross Weight with Packaging	0.26
Height	3 in
Hub Size	1/2"
Length	5 in
Weight	0.26 lb
Width	2 in

Certifications and Compliance

CSA File Number	LR11852
Hazardous Rating(s)	Suitable for use in hazardous location applications when installed according to NEC Articles 501.10(b) (Class I, Division 2) or 502.10, 503.10, and 505.15 (Class I Zone 2).
UL File Number	E3397

Logistics

Carton Quantity	10
-----------------	----

Product Assets

3D Models - OLB-1 3D Model (STP)
Catalogs - Killark Catalog
Certifications - E Series, O Series, CO & TW Series Conduit Bodies CSA Certificate of Conformity
Customer Notices - Prop 65 Notice
Engineering Drawing - OLB-1 Engineering Drawing (DWG)
Sales Drawings - OLB-1 Sales Drawing (PDF)



A proud member of the Hubbell Family.