



# OLR-3 - 1" LR Hub O Conduit Body

By Killark  
Catalog # [OLR-3](#)

1" LR Hub O Series Conduit Body.



\*Representative Image

### Features

- Raintight when used with gasketed covers.
- Malleable iron suitable for use in concrete.
- Interchangeable with competitive products.
- Stainless steel screws on stamped and cast covers.
- Tapered threaded hubs (NPT).

### Application

To provide access to conductors for pulling, splicing, and maintenance. Threaded for rigid conduit and IMC.

### General

Color	<ul style="list-style-type: none"><li>• Gray</li><li>• Gris</li></ul>
Finish Type	Peinture époxy en poudre
Hub Pattern	LR
Material	Aluminum, Copper Free (less than 4/10 of 1%)
Series	O Series
Type	<ul style="list-style-type: none"><li>• Conduit Body</li><li>• Conduit Body</li></ul>
UPC	783936490533

### Dimensions

Dimensions	7 in x 3 in x 2 in
Gross Weight with Packaging	0.54
Height	2 in
Hub Size	1"
Length	7 in
Weight	0.54 lb
Width	3 in

### Certifications and Compliance

CSA File Number	LR11852
Hazardous Rating(s)	Suitable for use in hazardous location applications when installed according to NEC Articles 501.10(b) (Class I, Division 2) or 502.10, 503.10, and 505.15 (Class I Zone 2).
UL File Number	E3397

### Logistics

Carton Quantity	5
-----------------	---

### Product Assets

- [3D Models - OLR-3 3D Model \(STP\)](#)
- [Catalogs - Killark Catalog](#)
- [Certifications - E Series, O Series, CO & TW Series Conduit Bodies CSA Certificate of Conformity](#)
- [Customer Notices - Prop 65 Notice](#)
- [Engineering Drawing - OLR-3 Engineering Drawing \(DWG\)](#)
- [Sales Drawings - OLR-3 Sales Drawing \(PDF\)](#)



A proud member of the Hubbell Family.