



OT-4 - 1 1/4" T Hub O Conduit Body

By Killark
Catalog # OT-4

1 1/4" T Hub O Series Conduit Body.



*Representative Image

Features

- Raintight when used with gasketed covers.
- Malleable iron suitable for use in concrete.
- Interchangeable with competitive products.
- Stainless steel screws on stamped and cast covers.
- Tapered threaded hubs (NPT).

Application

To provide access to conductors for pulling, splicing, and maintenance. Threaded for rigid conduit and IMC.

General

Color	<ul style="list-style-type: none">• Gray• Gris
Finish Type	Peinture époxy en poudre
Hub Pattern	T
Material	Aluminum, Copper Free (less than 4/10 of 1%)
Series	O Series
Type	<ul style="list-style-type: none">• Conduit Body• Conduit Body
UPC	783936530048

Dimensions

Dimensions	10.25 in x 5 in x 5.375 in
Gross Weight with Packaging	1.55
Height	5.375 in
Hub Size	1-1/4"
Length	10.25 in
Weight	1.55 lb
Width	5 in

Certifications and Compliance

CSA File Number	LR11852
Hazardous Rating(s)	Suitable for use in hazardous location applications when installed according to NEC Articles 501.10(b) (Class I, Division 2) or 502.10, 503.10, and 505.15 (Class I Zone 2).
UL File Number	E3397

Product Assets

[3D Models - OT-4 3D Model \(STP\)](#)
[Catalogs - Killark Catalog](#)
[Certifications - E Series, O Series, CO & TW Series Conduit Bodies CSA Certificate of Conformity](#)
[Customer Notices - Prop 65 Notice](#)
[Engineering Drawing - OT-4 Engineering Drawing \(DWG\)](#)
[Sales Drawings - OT-4 Sales Drawing \(PDF\)](#)



A proud member of the Hubbell Family.

©2024 Hubbell Incorporated. All rights reserved.
KILL_CA-OT-4-SPEC-EN | REV 1/2024