



OTB-5 - 1-1/2" TB Hub, Aluminum O Series Conduit Body

By Killark
Catalog # [OTB-5](#)

1-1/2" TB Hub, Aluminum O Series Conduit Body



Features

- Raintight when used with gasketed covers.
- Malleable iron suitable for use in concrete.
- Interchangeable with competitive products.
- Stainless steel screws on stamped and cast covers.
- Tapered threaded hubs (NPT).

Application

To provide access to conductors for pulling, splicing, and maintenance. Threaded for rigid conduit and IMC.

Specifications

UL File Number	E3397
CSA File Number	LR11852
Hazardous Rating(s)	Suitable for use in hazardous location applications when installed according to NEC Articles 501.10(b) (Class I, Division 2) or 502.10, 503.10, and 505.15 (Class I Zone 2).
EU RoHS Indicator	Contact Manufacturer

Configuration

Hub Pattern	TB
-------------	----

Dimensions

Height	5.125 in
Width	5 in
Hub Size	1-1/2"
Length	10.25 in
Gross Weight with Packaging	1.63
Dimensions	10.25 in x 5 in x 5.125 in

General

Color	Gray
UPC	783936530154
Type	Conduit Body
Material	Aluminum, Copper Free (less than 4/10 of 1%)
Series	O Series

Product Assets

[Catalog \[English\]](#)