



OX-6 - 2" X Hub, Aluminum O Series Conduit Body

By Killark
Catalog # OX-6

2" X Hub, Aluminum O Series Conduit Body

Features

- Raintight when used with gasketed covers.
- Malleable iron suitable for use in concrete.
- Interchangeable with competitive products.
- Stainless steel screws on stamped and cast covers.
- Tapered threaded hubs (NPT).

Application

To provide access to conductors for pulling, splicing, and maintenance. Threaded for rigid conduit and IMC.

Specifications

CSA File Number	LR11852
EU RoHS Indicator	Contact Manufacturer
UL File Number	E3397
Hazardous Rating(s)	Suitable for use in hazardous location applications when installed according to NEC Articles 501.10(b) (Class I, Division 2) or 502.10, 503.10, and 505.15 (Class I Zone 2).

Configuration



Hub Pattern	X
Dimensions	
Hub Size	2"
Length	12 in
Height	4 in
Width	6 in
Gross Weight with Packaging	2.5
Dimensions	12 in x 6 in x 4 in
General	
Color	Gray
Series	O Series
UPC	783936550060
Type	Conduit Body
Material	Aluminum, Copper Free (less than 4/10 of 1%)
Logistics	
Carton Quantity	2
Product Assets	
Catalog [English]	