



R-52 - 1½" to ¾" Reducing Bushing

By Killark
Catalog # [R-52](#)

1½" to ¾" Reducing Bushing



Features

- Tapered threads (NPT)
- Smooth internal bushing protects conductors
- Threaded for Rigid Conduit or IMC

Application

To reduce the trade size of a taped hole or hub.

Specifications

CSA File Number	LR11716
EU RoHS Indicator	Contact Manufacturer
UL File Number	E10514
Hazardous Rating(s)	• Class I, Divisions 1 & 2, Groups A, B, C, D • Class I, Zones 1 & 2, Groups IIC, IIB, IIA • Class II, Divisions 1 & 2, Groups E, F, G

Dimensions

Hub Size	1-1/2" to 3/4"
----------	----------------

Length	1.9 in
Weight	0.18 lb.
Height	0.83 in
Width	1.9 in
Gross Weight with Packaging	0.18
Dimensions	1.9 in x 1.9 in x 0.83 in

General

Color	Silver
Series	R Series
UPC	783936570082
Type	Reducing Bushing
Material	Aluminum, Copper Free (less than 4/10 of 1%)
Finish Type	Natural

Logistics

Carton Quantity	20
-----------------	----

Product Assets

[Installation Manual \[English\]](#)