



R-53 - 1-1/2" to 1" Reducing Bushing, Aluminum

By Killark
Catalog # [R-53](#)

1-1/2" to 1" Reducing Bushing, Aluminum



Features

- Tapered threads (NPT)
- Smooth internal bushing protects conductors
- Threaded for Rigid Conduit or IMC

Application

To reduce the trade size of a taped hole or hub.

Specifications

CSA File Number	LR11716
EU RoHS Indicator	Contact Manufacturer
UL File Number	E10514
Hazardous Rating(s)	• Class I, Divisions 1 & 2, Groups A, B, C, D • Class I, Zones 1 & 2, Groups IIC, IIB, IIA • Class II, Divisions 1 & 2, Groups E, F, G

Dimensions

Hub Size	1-1/2" to 1"
----------	--------------

Length	1.9 in
Weight	0.14 lb.
Height	0.99 in
Width	1.9 in
Gross Weight with Packaging	0.14
Dimensions	1.9 in x 1.9 in x 0.99 in

General

Color	Silver
Series	R Series
UPC	783936570099
Type	Reducing Bushing
Material	Aluminum, Copper Free (less than 4/10 of 1%)
Finish Type	Natural

Logistics

Carton Quantity	20
-----------------	----

Product Assets

[Installation Manual \[English\]](#)