KILLARK®

UGR Series 20A 125V Acceptor Receptacle Quick-Wire, 1/2" Dead End

By Killark
Catalog # UGR1-20231QW

20A 125V Acceptor Receptacle Quick-Wire, 1/2" Dead End



Features

- Factory sealed chamber in UGR receptacle contains switch's arcing components.
- Spring loaded receptacle cover closes when plug is removed.
- Copper-free aluminum (less than 4/10 of 1%) alloy resists corrosion
- Electrostatically applied and baked powder epoxy/polyester finish
- ACCEPTOR® plugs conform to NEMA configurations, while it's "turn to engage" feature locks in plug and can be used to prevent accidental disengagement of critical equipment.
- Plugs for use with type S/SO/ST/STO heavy duty cord.

Specifications

Nema Rating	3, 7(C, D), 9(F, G)
Buy America(n) Qualified	Contact Manufacturer
Hazardous Rating(s)	• Class I, Divisions 1 & 2, Groups C, D • Class I, Zones 1 & 2, Groups IIB, IIA • Class II, Divisions 1 & 2, Groups F, G • Class III, Divisions 1 & 2
EU RoHS Indicator	Contact Manufacturer

Conductor

Number Of Poles	2
Number Of Wires	3

Configuration

Hub Pattern	Dead-End

Current

Amperage Rating	20 A

Dimensions

Hub Size	1/2"

General

UPC	783936125022
Type	Straight Blade
Receptacle Type	Delayed Action
Material	Aluminum, Copper Free (less than 4/10 of 1%)
Series	UGR Series

Logistics

Factory Sealed	Factory Sealed

Product Assets

Catalog [English]

© 2026 Hubbell Incorporated. All rights reserved