



UGRGF Series 20A, 125V GFI Protected Receptacle, 1/2" Dead End

By Killark
Catalog # [UGRGF107](#)

20A, 125V GFI Protected Receptacle, 1/2" Dead End.



*Representative Image

Features

- Factory Sealed.
- Test and Reset push buttons are provided on cover assembly.
- Includes new GFCI to meet latest UL943 GFCI standards revisions.
- Exterior gasket provides NEMA 3 weatherproof protection.
- Ground boss for grounding in the splice box.
- Color coded wiring and stainless steel cover bolts.
- Receptacle used is UGR0-20231QW.
- Unit should be tested monthly.

General

Catalog Number	UGRGF107
EU RoHS Indicator	Contact Manufacturer
Number Of Poles	2
Series	UGRGF
UPC	783936784526

Dimensions

Hub Size	1/2"
Weight	7.5 lb

Electrical Ratings

Amperage Rating	20
Voltage Rating	125 VAC

Conductor Related

Number Of Wires	3
-----------------	---

Certifications And Compliance

CSA File Number	LR11714
Hazardous Rating(s)	Class 1, Divisions 1 & 2, Groups C, D Class I, Zones 1 & 2, Groups IIB, IIA Class II, Divisions 1 & 2, Groups F, G Class III, Divisions 1 & 2
Nema Rating	3, 7(C, D), 9(F, G)

Product Assets

[Certifications - UGRGF Series CSA Certificate of Compliance](#)



A Hubbell brand

©2024 Hubbell Incorporated. All rights reserved
KILL_CA-UGRGF107-SPEC-EN | REV 6/2024