KILLARK®

VBQ Series Hazardous Interlocked Receptacle - Square D - FAL Series 60A Breaker 3P 4W



By Killark
Catalog # VBQ6034SN60

Square D - FAL Series 60A Receptacle 60A Breaker 3W4P

Features

- Plug Interlock Mechanism for Dead-Front construction. Switch cannot be turned “ON” without fully inserted plug. Plug cannot be removed with switch in “ON” position
- Ground Fault Options Available
- Spacious wiring room that meets NEC wire bending requirements.
- Adjustable mounting lugs
- Quick Release Cover Bolts with Triple Leads for faster removal
- Electrostatically applied polyester/epoxy finish
- Breaker Handle has provisions for locking “ON” or “OFF” with up to three Padlocks

Specifications

Nema Rating	7 (C, D)
Buy America(n) Qualified	Contact Manufacturer
Hazardous Rating(s)	• Class I, Division 2, Groups B, C, D • Class I, Zone 2, Groups IIB+H2, IIA • Class II, Divisions 1 & 2, Groups F, G • Class III, Divisions 1 & 2

Conductor

Number Of Poles	3
Number Of Wires	4

Configuration

Hub Pattern	Dead-End

Current

Amperage Rating	60 A

Dimensions

Hub Size	1-1/2"

General

Product Family	Plugs & Receptacles
UPC	783936835273
Type	Pin & Sleeve
Receptacle Type	Mechanically Interlocked
Material	Aluminum, Copper Free (less than 4/10 of 1%)
Series	VBQ Series

Product Assets

Catalog [English]

© 2026 Hubbell Incorporated. All rights reserved