



Versamate Series 30A 3 Pole 3 Wire Plug Assembly - AT Type

By Killark
Catalog # [VP3033](#)

30A 3 Pole 3 Wire Plug Assembly - AT Type.

Features

- Feature an octagonal body style, ensuring a sure grip when connecting or disconnecting.
- Insulators have high mechanical and dielectric strength.
- “Increased Safety” type box terminals with gripper ribs securely clamp around conductors.
- Funneled conductor entry chambers lead all properly stripped conductors into terminals simultaneously.
- Type 4X rating when inserted into VersaMate receptacle and locking ring is tightened.
- Includes suitability for Type P marine cable.

General

Application	
Catalog Number	VP3033
EU RoHS Indicator	Contact Manufacturer
Finish Type	Finition époxy/polyester en poudre cuite
Grommet Range	0.55-1.20
Material	Body-Copper-free aluminum; Contacts-Brass; Spring tensioner-Patented beryllium copper; External screws-316 stainless steel
Series	VersaMate
Style	Style I
Type	
UPC	783936077772

Dimensions

Dimensions	6.68 in x 3 in x 3 in
Height	3 in
Length	6.68 in
Width	3 in

Electrical Ratings

Amperage Rating	30 A
Frequency Rating	50-400 Hz
Voltage Rating	600 VAC
	250 VDC

Conductor Related

Number Of Wires	3
-----------------	---

Product Assets

[Customer Notices - Prop 65 Notice](#)
[Installation Manuals - Versamate 30 Amp Allen Terminal IOM K1381](#)





A Hubbell brand

©2024 Hubbell Incorporated. All rights reserved
KILL_CA-VP3033-SPEC-EN | REV 6/2024