



VSQ Series 30A 3P 4W Hazardous Interlocked Receptacle

By Killark
Catalog # VSQ3034

30A 3W4P VSQ Hazardous Interlocked Receptacle.



*Representative Image

General

Ambient Temp. Range	-20°C to 40 °C (T5) -20°C to 40 °C (T6) -20°C to 40 °C
Catalog Number	VSQ3034
Color	
EU RoHS Indicator	Contact Manufacturer
Hub Pattern	Feed-Thru
Material	Aluminum
Number Of Poles	3
Receptacle Type	Mechanically Interlocked
Series	VSQ
Style	3 Pole, 4-Wire
Type	
UPC	783936833323

Dimensions

Hub Size	1"
Weight	13.31 lb

Electrical Ratings

Amperage Rating	30 A
Voltage Rating	Up to 600 V

Conductor Related

Number Of Wires	4
-----------------	---

Certifications And Compliance

Hazardous Rating(s)	Class I, Divisions 1 & 2, Groups B, C, D Class I, Zones 1 & 2, Groups IIB+H2, IIA Class II, Divisions 1 & 2, Groups F, G Class III, Divisions 1 & 2
Nema Rating	3, 4, 4X, 7(B, C, D), 9(F, G)

Product Assets

[Certifications - 30A VSQ Series UL Certification](#)
[Customer Notices - Prop 65 Notice](#)
[Installation Manuals - 30A VSQ Series IOM K1217](#)



A Hubbell brand

©2024 Hubbell Incorporated. All rights reserved
KILL_CA-VSQ3034-SPEC-EN | REV 6/2024