KILLARK®

VSQ Series 60A 3P 4W Hazardous Interlocked Receptacle

By Killark
Catalog # VSQ6034

60A 3W4P VSQ Hazardous Interlocked Receptacle



Features

- Compact size and footprint
- Plug Interlock Mechanism for Dead-Front construction. Switch cannot be turned “ON” without fully inserted plug. Plug cannot be removed with switch in “ON” position
- Factory Wired Receptacle (Load Side)
- “Off” position is padlockable for maintenance safety
- Auxiliary Contact (late-make early-break) rated 10 Amp, 1/3 HP at 125/250 VAC.
- Adjustable mounting lugs
- Feed-through construction
- Horsepower-rated internal switch

Specifications

Nema Rating	3, 4, 4X, 7(B, C, D), 9(F, G)
Hazardous Rating(s)	• Class I, Divisions 1 & 2, Groups B, C, D • Class I, Zones 1 & 2, Groups IIB+H2, IIA • Class II, Divisions 1 & 2, Groups F, G • Class III, Divisions 1 & 2
EU RoHS Indicator	Contact Manufacturer

Conductor

Number Of Poles	3
Number Of Wires	4

Configuration

Hub Pattern	Feed-Thru

Current

Amperage Rating	60 A

Dimensions

Weight	29 lb.
Hub Size	1″

General

UPC	783936833347
Type	Pin & Sleeve
Receptacle Type	Mechanically Interlocked
Material	Aluminum, Copper Free (less than 4/10 of 1%)
Series	VSQ Series

Product Assets

Installation Manual [English]

© 2026 Hubbell Incorporated. All rights reserved