



# VSQ Series 60A 3P 4W Hazardous Interlocked Receptacle

By Killark  
Catalog # [VSQ6034](#)

60A 3W4P VSQ Hazardous Interlocked Receptacle



## Features

- Compact size and footprint
- Plug Interlock Mechanism for Dead-Front construction. Switch cannot be turned "ON" without fully inserted plug. Plug cannot be removed with switch in "ON" position
- Factory Wired Receptacle (Load Side)
- "Off" position is padlockable for maintenance safety
- Auxiliary Contact (late-make early-break) rated 10 Amp, 1/3 HP at 125/250 VAC.
- Adjustable mounting lugs
- Feed-through construction
- Horsepower-rated internal switch

## Specifications

Hazardous Rating(s)	<ul style="list-style-type: none"> <li>• Class I, Divisions 1 &amp; 2, Groups B, C, D</li> <li>• Class I, Zones 1 &amp; 2, Groups IIB+H2, IIA</li> <li>• Class II, Divisions 1 &amp; 2, Groups F, G</li> <li>• Class III, Divisions 1 &amp; 2</li> </ul>
EU RoHS Indicator	Contact Manufacturer
Nema Rating	3, 4, 4X, 7(B, C, D), 9(F, G)

## Conductor

Number Of Wires	4
Number Of Poles	3

## Configuration

Hub Pattern	Feed-Thru
-------------	-----------

## Current

Amperage Rating	60 A
-----------------	------

## Dimensions

Hub Size	1"
Weight	29 lb.

## General

Receptacle Type	Mechanically Interlocked
Type	Pin & Sleeve
Series	VSQ Series
Material	Aluminum, Copper Free (less than 4/10 of 1%)
UPC	783936833347

## Product Assets

[Installation Manual \[English\]](#)