



XCS-OB4 - XCS Series, AL Momentary Contact Double Push Button Cvr w/ Device, Green Button w/ Start Nameplate, Red Button w/ Stop Nameplate, 1NO/1NC

By Killark
Catalog # XCS-OB4

XCS Series - Aluminum Momentary Contact Double Push Button Cover With Device - Green Button With "Start" Nameplate - Red Button With "Stop" Nameplate - 1NO/1NC Contact Rating

Features

- Copper free cast aluminum alloy.
- Ground flange joint between bolted cover and box provide required flame path.
- Push button, selector switches and pilot light operator bodies are copper-free aluminum.
- Operating shaft in both push buttons and selector switches are stainless steel.

Application

Hazardous locations due to the presence of flammable gases or vapors, combustible dusts, or easily ignitable fiber or flyings. Installations at petroleum refineries, chemical and petrochemical plants, and other processing or storage facilities where simil

Specifications

UL File Number	E53360
Buy America(n) Qualified	Contact Manufacturer
CSA File Number	LR11714
Hazardous Rating(s)	• Class I, Divisions 1 & 2, Groups C, D • Class I, Zones 1 & 2, Groups IIB, IIA • Class II, Divisions 1 & 2, Groups E, F, G • Class III, Divisions 1 & 2
EU RoHS Indicator	Contact Manufacturer
Conductor	
Number Of Poles	2
Configuration	
Back Box Type	SWB
Current	
Frequency Rating	50/60 Hz



Amperage Rating	10 A
Contact Rating	• 60A INRUSH @ 120 VAC • 30A INRUSH @ 240 VAC • 15A INRUSH @ 480 VAC • 12A INRUSH @ 600 VAC • 6A BREAKING @ 120 VAC • 3A BREAKING @ 240 VAC • 1.5A BREAKING @ 480 VAC • 1.2A BREAKING @ 600 VAC • 10A CARRYING @ 120 VAC • 10A CARRYING @ 240 VAC • 10A CARRYING @ 480 VAC

Dimensions

Height	4.375 in
Width	6 in
Length	6.375 in
Gross Weight with Packaging	1.33
Depth	1-3/4 in
Dimensions	6.375 in x 6 in x 4.375 in

General

Color	Green-Red
UPC	783936890081
Type	Aluminum Cover With Two Push Buttons
Material Series	Copper-free aluminum XCS Series

Operational

Actuator Action	Momentary Pushbutton SP (per circuit)
-----------------	--

Product Assets

[Catalog \[English\]](#)
[Installation Manual \[French, English\]](#)