



XCS-OB4 - XCS Series, AL Momentary Contact Double Push Button Cvr w/ Device, Green Button w/ Start Nameplate, Red Button w/ Stop Nameplate, 1NO/1NC

By Killark
Catalog # [XCS-OB4](#)

XCS Series - Aluminum Momentary Contact Double Push Button
Cover With Device - Green Button With "Start" Nameplate - Red
Button With "Stop" Nameplate - 1NO/1NC Contact Rating.



*Representative Image

General

Action	SP (per circuit)
Actuator	Momentary Pushbutton
Application	
Back Box Type	SWB
Catalog Number	XCS-OB4
Color	
EU RoHS Indicator	Contact Manufacturer
Material	Copper-free aluminum
Number Of Poles	2
Series	XCS
Type	
UPC	783936890081

Dimensions

Depth	1-3/4
Dimensions	6.375 in x 6 in x 4.375 in
Gross Weight with Packaging	1.33
Height	4.375 in
Length	6.375 in
Width	6 in

Electrical Ratings

Amperage Rating	10 A
Contact Rating	60A INRUSH @ 120 VAC; 30A INRUSH @ 240 VAC; 15A INRUSH @ 480 VAC; 12A INRUSH @ 600 VAC; 6A BREAKING @ 120 VAC; 3A BREAKING @ 240 VAC; 1.5A BREAKING @ 480 VAC; 1.2A BREAKING @ 600 VAC; 10A CARRYING @ 120 VAC; 10A CARRYING @ 240 VAC; 10A CARRYING @ 480 VAC;
Frequency Rating	50/60 Hz

Certifications And Compliance

CSA File Number	LR11714
Hazardous Rating(s)	Class I, Divisions 1 & 2, Groups C, D Class I, Zones 1 & 2, Groups IIB, IIA Class II, Divisions 1 & 2, Groups E, F, G Class III, Divisions 1 & 2
UL File Number	E53360

Product Assets

[Certifications - FXCS & XCS Series Auxiliary Devices UL
Certification](#)
[Customer Notices - Prop 65 Notice](#)
[Installation Manuals - SWB Series Control Stations IOM K0569F](#)



A Hubbell brand

©2024 Hubbell Incorporated. All rights reserved
KILL_CA-XCS0B4-SPEC-EN | REV 6/2024