



XCS-OMMR7 - XCS Series, AL Maintained Contact Push/Pull Button Cvr w/ Device, Red Mushroom Button w/ 3 Nameplates, Start/Stop, Blank, Emerg Stop, 2NC

By Killark
Catalog # [XCS-OMMR7](#)

XCS Series - Aluminum Maintained Contact Push/Pull Button Cover With Device - Red Mushroom Button Supplied With Three Nameplates("Start/Stop", Blank, "Emergency Stop") - 2NC Contact Rating

Features

- Copper free cast aluminum alloy.
- Ground flange joint between bolted cover and box provide required flame path.
- Push button, selector switches and pilot light operator bodies are copper-free aluminum.
- Operating shaft in both push buttons and selector switches are stainless steel.

Application

Hazardous locations due to the presence of flammable gases or vapors, combustible dusts, or easily ignitable fiber or flyings. Installations at petroleum refineries, chemical and petrochemical plants, and other processing or storage facilities where simil

Specifications

UL File Number	E53360
Buy America(n) Qualified	Contact Manufacturer
CSA File Number	LR11714
Hazardous Rating(s)	• Class I, Divisions 1 & 2, Groups C, D • Class I, Zones 1 & 2, Groups IIB, IIA • Class II, Divisions 1 & 2, Groups E, F, G • Class III, Divisions 1 & 2
EU RoHS Indicator	Contact Manufacturer
Conductor	
Number Of Poles	1
Configuration	
Back Box Type	SWB



Current

Frequency Rating	50/60 Hz
Amperage Rating	10 A
Contact Rating	• 60A INRUSH @ 120 VAC • 30A INRUSH @ 240 VAC • 15A INRUSH @ 480 VAC • 12A INRUSH @ 600 VAC • 6A BREAKING @ 120 VAC • 3A BREAKING @ 240 VAC • 1.5A BREAKING @ 480 VAC • 1.2A BREAKING @ 600 VAC • 10A CARRYING @ 120 VAC • 10A CARRYING @ 240 VAC • 10A CARRYING @ 480 VAC

Dimensions

Gross Weight with Packaging	1.4
Depth	3-1/8 in

General

Color	Red
UPC	783936376370
Type	Aluminum Cover With Push-Pull Button
Material	Copper-free aluminum
Series	XCS Series

Operational

Actuator	Maintained Pushbutton
Action	SP

Product Assets

[Catalog \[English\]](#)