

## XCS-2B3 - XCS Series, AL Dead-End Momentary Contact Single Push Button Ctrl Stn, Black Button w/ Nameplate, Hub 3/4", 1NO/1NC Contact Rating

By Killark

Catalog # [XCS-2B3](#)



\*Representative Image

XCS Series - Aluminum Dead-End Momentary Contact Single Push Button Control Station - Black Button With Nameplate To Be Specified - Hub Size 3/4Inch - 1NO/1NC Contact Rating.

### Features

- Copper free cast aluminum alloy.
- Ground flange joint between bolted cover and box provide required flame path.
- Push button, selector switches and pilot light operator bodies are copper-free aluminum.
- Operating shaft in both push buttons and selector switches are stainless steel.

### General

Action	Momentary
Actuator	Single Pushbutton
Ambient Temp. Range	UL: -25 to 40 °C, CSA: -50 to 40 °C, IEC: -20 to 40 °C
Application	SWB
Back Box Type	XCS-2B3
Catalog Number	Black
Color	Noir
EU RoHS Indicator	Contact Manufacturer
Number Of Poles	1
Series	XCS
Type	
UPC	783936890876

### Dimensions

Depth	4-1/32
Gross Weight with Packaging	2.6

### Electrical Ratings

Amperage Rating	10 A
Contact Rating	60A INRUSH @ 120 VAC; 30A INRUSH @ 240 VAC; 15A INRUSH @ 480 VAC; 12A INRUSH @ 600 VAC; 6A BREAKING @ 120 VAC; 3A BREAKING @ 240 VAC; 1.5A BREAKING @ 480 VAC; 1.2A BREAKING @ 600 VAC; 10A CARRYING @ 120 VAC; 10A CARRYING @ 240 VAC; 10A CARRYING @ 480 VAC; 50/60 Hz
Frequency Rating	50/60 Hz

### Certifications And Compliance

CSA File Number	LR11714
Hazardous Rating(s)	Class I, Divisions 1 & 2, Groups C, D
	Class I, Zones 1 & 2, Groups IIB, IIA
	Class II, Divisions 1 & 2, Groups E, F, G
	Class III, Divisions 1 & 2
UL File Number	E53360

### Product Assets

Certifications - FXCS & XCS Series Auxiliary Devices UL Certification
Customer Notices - Prop 65 Notice



**A Hubbell brand**

©2024 Hubbell Incorporated. All rights reserved  
KILL\_CA-XCS2B3-SPEC-EN | REV 6/2024