

XEDS-30A - XEDS Series, 30 Amp Max, Non-Fused Disconnect Switch W/ 1 Aux Contact

By Killark

Catalog # [XEDS-30A](#)

XEDS Series, 30 Amp Max, Non-Fused Disconnect Switch W/ 1 Aux Contact.



*Representative Image

Features

- External handle is vault type with standard provisions for locking in "OFF" position with up to three padlocks.
- Provisions for locking in "ON" position available as factory modification (add suffix SU40 to catalog number).
- Enclosure and external handle is cast copper-free aluminum alloy (less than 4/10 of 1%).
- Cover bolts are stainless steel.
- Eaton (Cutler Hammer) Type DS Switches.
- Two cast conduit hubs, one top and one bottom.
- Internal disconnect handle mechanism is a sliding plate mounted to the cover.

General

EU RoHS Indicator	Contact Manufacturer
Enclosure Type	Bolted
Material	Aluminum, Copper Free (less than 4/10 of 1%)
Mounting Type	Wall
Number Of Poles	3
Operating Temperature Celcius Max	40 Degree
Series	XEDS
Type	<ul style="list-style-type: none">Non-Fused DisconnectNon-Fused Disconnect
UPC	783936897998

Dimensions

Depth	6.875
Height	11.875 in
Weight	11 lb
Width	8.75 in

Electrical Ratings

Frequency Rating	60 Hz
Primary Voltage	600 VAC/250 VDC

Conductor Related

Number Of Wires	4
-----------------	---

Certifications and Compliance

CSA File Number	LR11714
Hazardous Rating(s)	<ul style="list-style-type: none">Class II, Divisions 1 & 2, Groups E, F, GClass III, Divisions 1 & 2
Nema Rating	3R, 4, 9(E, F, G)
UL File Number	E53290

Product Assets

Certifications - DEDS & XEDS Series UL Certification
Customer Notices - Prop 65 Notice



A proud member of the Hubbell Family.