



XEDS-60A - XEDS Series, 60 Amp Max, Non-Fused Disconnect Switch W/ 1 Aux Contact

By Killark
Catalog # [XEDS-60A](#)

XEDS Series, 60 Amp Max, Non-Fused Disconnect Switch W/ 1 Aux Contact

Features

- External handle is vault type with standard provisions for locking in "OFF" position with up to three padlocks.
- Provisions for locking in "ON" position available as factory modification (add suffix SU40 to catalog number).
- Enclosure and external handle is cast copper-free aluminum alloy (less than 4/10 of 1%).
- Cover bolts are stainless steel.
- Eaton (Cutler Hammer) Type DS Switches.
- Two cast conduit hubs, one top and one bottom.
- Internal disconnect handle mechanism is a sliding plate mounted to the cover.

Specifications

Nema Rating	3R, 4, 9(E, F, G)
UL File Number	E53290
CSA File Number	LR11714
Hazardous Rating(s)	• Class II, Divisions 1 & 2, Groups E, F, G • Class III, Divisions 1 & 2
EU RoHS Indicator	Contact Manufacturer

Conductor

Number Of Poles	3
-----------------	---



Number Of Wires	4
Current	
Frequency Rating	60 Hz
Primary Voltage	600 VAC/250 VDC

Dimensions	
Weight	17 lb.
Height	16 in
Width	9.125 in
Depth	7 in

General	
Mounting Type	Wall
UPC	783936898070
Type	Non-Fused Disconnect
Enclosure Type	Bolted
Material	Aluminum, Copper Free (less than 4/10 of 1%)
Series	XEDS Series

Operational	
Operating Temperature Celcius Max	40 Degree