



XMSW-1CT - Manual Motor Starter - NEMA Size 1 - 3-Pole; 3Ø, Ac

By Killark
Catalog # XMSW-1CT

Manual Motor Starter - NEMA Size 1 - 3-Pole; 3Ø, Ac



Features

- Rectangular bolted cover design provides for attractive, compact, uniform installations.
- Enclosure and external handle are diecast copper-free (less than 0.4%) aluminum alloy.
- Cast “ON,” “OFF,” “TRIPPED” markings on cover align with external handle and provide clear indication of enclosed starter condition.
- External handle is a vault type with standard provisions for locking in the “OFF” position with up to three pad-locks.
- Provision for locking in “ON” position is available as factory modification (add suffix SU-40 to catalog number).
- Two cast 1” NPT conduit hubs with integral pipe stop, one top and one bottom, are standard on all assemblies.

Specifications

UL File Number	E12379
Hazardous Rating(s)	• Class I, Divisions 1 & 2, Groups C, D • Class I, Zones 1 & 2, Groups IIB, IIA

EU RoHS Indicator

Current

Voltage Rating	600 V
----------------	-------

Dimensions

Size	1
------	---

General

UPC	783936912585
Series	XMSW Series

Operational

Horsepower - Maximum	10
----------------------	----

Product Assets

[Catalog Page \[English\]](#)

- Class II, Divisions 1 & 2, Groups E, F, G
 - Class III, Divisions 1 & 2
- Contact Manufacturer