

## XMSW-1CT

By Killark  
Catalog # [XMSW-1CT](#)

Manual Motor Starter - NEMA Size 1 - 3-Pole; 3Ø, Ac.



\*Representative Image

### Features

- Rectangular bolted cover design provides for attractive, compact, uniform installations.
- Enclosure and external handle are diecast copper-free (less than 0.4%) aluminum alloy.
- Cast "ON," "OFF," "TRIPPED" markings on cover align with external handle and provide clear indication of enclosed starter condition.
- External handle is a vault type with standard provisions for locking in the "OFF" position with up to three pad-locks.
- Provision for locking in "ON" position is available as factory modification (add suffix SU-40 to catalog number).
- Two cast 1" NPT conduit hubs with integral pipe stop, one top and one bottom, are standard on all assemblies.

### General

EU RoHS Indicator	Contact Manufacturer
Horsepower - Maximum	10
Series	XMSW
Size	1
UPC	783936912585

### Electrical Ratings

Voltage Rating 600 V

### Certifications and Compliance

Hazardous Rating(s)	<ul style="list-style-type: none"><li>Class I, Divisions 1 &amp; 2, Groups C, D</li><li>Class I, Zones 1 &amp; 2, Groups IIB, IIA</li><li>Class II, Divisions 1 &amp; 2, Groups E, F, G</li><li>Class III, Divisions 1 &amp; 2</li></ul>
---------------------	--

UL File Number E12379

### Product Assets

[Certifications - XMSW Series UL Certification](#)  
[Customer Notices - Prop 65 Notice](#)



A proud member of the Hubbell Family.