



XS Series 3-Way/SPDT (No Center Off) Tumbler Switch Cover With Device - 20A

By Killark
Catalog # [XS-3C](#)

XS Series - Aluminum 3-Way/SPDT (No Center Off) Tumbler
Switch Cover With Device - 20A



Features

- Front lever rotary operated switch assemblies.
- Standard provisions for padlocking in either “ON” or “OFF” position.
- The lever is connected to a threaded stainless steel shaft which passes through the cover.

Application

Used where making, breaking, or changing connections in an electric circuit is required.

Specifications

UL File Number	E53360
Buy America(n) Qualified	Contact Manufacturer
CSA File Number	LR11712
Hazardous Rating(s)	• Class I, Divisions 1 & 2, Groups C, D • Class I, Zones 1 & 2, Groups IIB, IIA • Class II, Divisions 1 & 2, Groups E, F, G • Class III, Divisions 1 & 2
EU RoHS Indicator	Contact Manufacturer

Conductor

Number Of Poles	1
-----------------	---

Configuration

Back Box Type	SWB
---------------	-----

Current

Frequency Rating	50/60 Hz
Amperage Rating	20 A

Dimensions

Height	4.25 in
Width	6.25 in
Length	6 in
Gross Weight with Packaging	1.26
Depth	4-1/4 in
Dimensions	6 in x 6.25 in x 4.25 in

General

Color	Gray
UPC	783936925127
Type	Aluminum Tumbler Switch Cover
Material	Aluminum, Copper Free (less than 4/10 of 1%)
Series	XS Series

Operational

Actuator	Lever
Action	SPDT (3-way)

Product Assets

[Catalog \[English\]](#)
[Installation Manual \[French, English\]](#)