



XSD-51 - XSD/XSX/FXSD/FXSX Series - XSD Single Gang Aluminum Manual Motor Starting Switch - 1 Pole Single Phase - Feed-Thru - Hub Size 3/4 In

By Killark
Catalog # [XSD-51](#)

XSD/XSX/FXSD/FXSX Series - XSD Single Gang Aluminum Manual Motor Starting Switch - 1 Pole Single Phase - Feed-Thru - Hub Size 3/4 In

Features

- Motor running protection when overload heaters are used.
- Enclosures are cast copper-free aluminum alloy.
- Operating shaft is stainless steel.
- Multiple gang assemblies available in combination with pilot lights, pushbuttons and switches on request.
- Ground flange joint between bolted cover and box provide required flame path.
- Provisions for padlocking switch in either "ON" or "OFF" position is standard.

Application

Provides manual starting and stopping of small AC or DC motors. Motor running protection when overload heaters are used.

Specifications

CSA File Number	LR11714
EU RoHS Indicator	Contact Manufacturer
UL File Number	E53360 / E12379
Hazardous Rating(s)	• Class I, Divisions 1 & 2, Groups C, D • Class I, Zones 1 & 2, Groups IIB, IIA • Class II, Divisions 1 & 2, Groups E, F, G • Class III, Divisions 1 & 2



Current

Frequency Rating	60 Hz
Power Factor	0.9
Voltage Rating	230 V

Dimensions

Length	3 in
Height	6 in
Width	4 in
Gross Weight with Packaging	2.4
Dimensions	3 in x 4 in x 6 in

General

Series	XSD Series
UPC	783936932170
Type	Aluminum Manual Motor Starting Switch With Overload Protection
Material	Copper-free aluminum

Operational

Horsepower - Maximum	1
----------------------	---

Product Assets

[Catalog Page \[English\]](#)
[Installation Manual \[French, English\]](#)