



XSX-53 - XSD/XSX/FXSD/FXSX Series - XSX Single Gang Aluminum Manual Motor Starting Switch - 3 Pole 3 Phase - Feed-Thru - Hub Size 3/4 In

By Killark
Catalog # [XSX-53](#)

XSD/XSX/FXSD/FXSX Series - XSX Single Gang Aluminum Manual Motor Starting Switch - 3 Pole 3 Phase - Feed-Thru - Hub Size 3/4 In

Features

- XSX Series (without overload protection) are ideally suited for across the-line applications where a positive disconnect means is required.
- Enclosures are cast copper-free aluminum alloy.
- Operating shaft is stainless steel.
- Multiple gang assemblies available in combination with pilot lights, pushbuttons and switches on request.
- Ground flange joint between bolted cover and box provide required flame path.
- Provisions for padlocking switch in either "ON" or "OFF" position is standard.

Application

Provides manual starting and stopping of small AC or DC motors. Motor running protection when overload heaters are used. XSX Series (without overload protection) is ideally suited for across-the-line applications where a positive disconnect means is requi

Specifications

CSA File Number	LR11714
EU RoHS Indicator	Contact Manufacturer
Hazardous Rating(s)	• Class I, Divisions 1 & 2, Groups C, D • Class I, Zones 1 & 2, Groups IIB, IIA • Class II, Divisions 1 & 2, Groups E, F, G



- Class III, Divisions 1 & 2

Current

Frequency Rating	60 Hz
Power Factor	0.9
Voltage Rating	600 V

Dimensions

Length	7.625 in
Height	4.125 in
Width	5.875 in
Gross Weight with Packaging	2.55
Dimensions	7.625 in x 5.875 in x 4.125 in

General

Series	XSX Series
UPC	783936933511
Type	Aluminum Manual Motor Starting Switch Without Overload Protection
Material	Copper-free aluminum

Operational

Horsepower - Maximum	10
----------------------	----

Product Assets

[Catalog Page \[English\]](#)