KILLARK®

ZN102CR-EX - 1/2" Nylon Cord Connector, 90° Bend, Cord Range .125-.187, Orange

By Killark
Catalog # ZN102CR-EX

1/2" Nylon Cord Connector, 90° Bend, Cord Range .125-.187, Orange



Features

- Nylon retention ring for increased holding power
- Neoprene bushing seals against moisture
- Nylon connectors obtain approximately the same retention values as metal cord connectors

Application

Durable nylon construction makes these connectors perfectly suited to corrosive environments. Typical applications for nylon cord connectors include food processing facilities, chemical and sewage treatment plants, and off-shore and dockside installations

Specifications

CSA File Number	LR73478
EU RoHS Indicator	Contact Manufacturer
UL File Number	E22698
Buy America(n) Qualified	Contact Manufacturer
Hazardous Rating(s)	Suitable for use in hazardous location applications when installed according to NEC Articles 501.10(b) (Class I, Division 2) or 502.10, 503.10, and 505.15 (Class I Zone 2).

Conductor

Cable Range	.125 - .187 in

Dimensions

Hub Size	1/2"
Length	2 in
Height	3 in
Width	1 in
Gross Weight with Packaging	0.5
Dimensions	2 in x 1 in x 3 in

General

Color	Gray
Color Code	Orange
Cord Range	.125-.187,
Series	Z-EX Series
UPC	783936972886
Type	90º Cord Connector
Material	Nylon
Finish Type	Natural

Logistics

Carton Quantity	25

Product Assets

Catalog [English]

© 2026 Hubbell Incorporated. All rights reserved