

**SAK Series**  
**Q 2 AKZ4**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
[www.weidmueller.com](http://www.weidmueller.com)

**Product image****Klippon® Connect with clamping yoke Technology**

The high reliability and variety of designs of the terminal blocks with clamping yoke connections make planning easier and optimises operational safety. Klippon® Connect provides a proven response to a range of different requirements.

**General ordering data**

|            |                                                                            |
|------------|----------------------------------------------------------------------------|
| Type       | Q 2 AKZ4                                                                   |
| Order No.  | <a href="#">0336400000</a>                                                 |
| Version    | SAK Series, Cross-connector, for cross-connection link, Number of poles: 2 |
| GTIN (EAN) | 4008190037680                                                              |
| Qty.       | 50 pc(s).                                                                  |

**SAK Series**  
**Q 2 AKZ4****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

www.weidmueller.com

**Technical data****Dimensions and weights**

|            |         |                 |            |
|------------|---------|-----------------|------------|
| Width      | 11.1 mm | Width (inches)  | 0.437 inch |
| Height     | 4 mm    | Height (inches) | 0.157 inch |
| Depth      | 9.9 mm  | Depth (inches)  | 0.39 inch  |
| Net weight | 1.538 g |                 |            |

**Temperatures**

|                           |               |                           |       |
|---------------------------|---------------|---------------------------|-------|
| Storage temperature, max. | 40 °C         | Storage temperature, min. | 10 °C |
| Storage temperature       | 10 °C...40 °C |                           |       |

**Material data**

|          |       |        |      |
|----------|-------|--------|------|
| Material | Cu Zn | Colour | grey |
|----------|-------|--------|------|

**System specifications**

|         |                           |
|---------|---------------------------|
| Version | for cross-connection link |
|---------|---------------------------|

**Additional technical data**

|                          |                 |                     |                 |
|--------------------------|-----------------|---------------------|-----------------|
| Explosion-tested version | No              | Installation advice | Direct mounting |
| Type of fixing           | when screwed in |                     |                 |

**Dimensions**

|                 |        |
|-----------------|--------|
| Pitch in mm (P) | 6.1 mm |
|-----------------|--------|

**Rating data**

|               |      |
|---------------|------|
| Rated current | 24 A |
|---------------|------|

**Classifications**

|             |             |            |             |
|-------------|-------------|------------|-------------|
| ETIM 6.0    | EC000489    | ETIM 7.0   | EC000489    |
| eClass 9.0  | 27-14-11-40 | eClass 9.1 | 27-14-11-40 |
| eClass 10.0 | 27-14-11-40 | UNSPSC     | 30-21-18-01 |

**Approvals**

Approvals



ROHS

Conform

**Downloads**

|                    |                                                 |
|--------------------|-------------------------------------------------|
| Brochure/Catalogue | <a href="#">CAT 1 TERM 16/17 EN</a>             |
| Engineering Data   | <a href="#">EPLAN, WSCAD, Zuken E3.S</a>        |
| Engineering Data   | <a href="#">STEP</a>                            |
| User Documentation | <a href="#">StorageConditionsTerminalBlocks</a> |