

**WQV 120/3****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Product image****Power feed-in**

Our wide range of W-Series terminal blocks with our WPD main line branch terminals, which are optimised to guarantee both convenience and space gains, ensures a secure and convenient connection at the power feed-in.

**General ordering data**

|            |                                                                                                                                          |
|------------|------------------------------------------------------------------------------------------------------------------------------------------|
| Version    | Cross-connector (terminal), when screwed in, Silver grey, 292 A, Number of poles: 3, Pitch in mm (P): 32.00, Insulated: No, Width: 10 mm |
| Order No.  | <a href="#">1063400000</a>                                                                                                               |
| Type       | WQV 120/3                                                                                                                                |
| GTIN (EAN) | 4008190141363                                                                                                                            |
| Qty.       | 5 pc(s).                                                                                                                                 |

## WQV 120/3

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Dimensions and weights

|            |         |                 |            |
|------------|---------|-----------------|------------|
| Depth      | 71.8 mm | Depth (inches)  | 2.827 inch |
| Height     | 76 mm   | Height (inches) | 2.992 inch |
| Width      | 10 mm   | Width (inches)  | 0.394 inch |
| Net weight | 224.2 g |                 |            |

## Temperatures

|                                  |                |                                  |               |
|----------------------------------|----------------|----------------------------------|---------------|
| Storage temperature              | -25 °C...55 °C | Ambient temperature              | -5 °C...40 °C |
| Continuous operating temp., min. | -50 °C         | Continuous operating temp., max. | 100 °C        |

## Material data

|                           |       |        |             |
|---------------------------|-------|--------|-------------|
| Material                  | PA 66 | Colour | Silver grey |
| UL 94 flammability rating | V-2   |        |             |

## System specifications

|         |                   |
|---------|-------------------|
| Version | For the terminals |
|---------|-------------------|

## Additional technical data

|                     |                 |                |                 |
|---------------------|-----------------|----------------|-----------------|
| Installation advice | Direct mounting | Type of fixing | when screwed in |
|---------------------|-----------------|----------------|-----------------|

## Cross-connector

|                                     |       |                       |                 |
|-------------------------------------|-------|-----------------------|-----------------|
| Number of cross-connected terminals | 3     | Rated current, 2-pole | 269 A           |
| Rated current, multi-pole           | 269 A | Type                  | Cross-connector |

## Dimensions

|                 |       |
|-----------------|-------|
| Pitch in mm (P) | 32 mm |
|-----------------|-------|

## General

|                     |                 |                 |   |
|---------------------|-----------------|-----------------|---|
| Installation advice | Direct mounting | Number of poles | 3 |
|---------------------|-----------------|-----------------|---|

## Rating data

|               |       |
|---------------|-------|
| Rated current | 292 A |
|---------------|-------|

## Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC000489    | ETIM 7.0    | EC000489    |
| ETIM 8.0    | EC000489    | ETIM 9.0    | EC000489    |
| ETIM 10.0   | EC000489    | ECLASS 9.0  | 27-14-11-40 |
| ECLASS 9.1  | 27-14-11-40 | ECLASS 10.0 | 27-14-11-40 |
| ECLASS 11.0 | 27-14-11-40 | ECLASS 12.0 | 27-14-11-40 |
| ECLASS 13.0 | 27-25-03-03 | ECLASS 14.0 | 27-25-03-03 |
| ECLASS 15.0 | 27-25-03-03 |             |             |

## Environmental Product Compliance

|                        |                             |
|------------------------|-----------------------------|
| RoHS Compliance Status | Compliant without exemption |
| REACH SVHC             | No SVHC above 0.1 wt%       |

Creation date May 15, 2025 1:32:56 PM CEST

Catalogue status 10.05.2025 / We reserve the right to make technical changes.

## WQV 120/3

**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Technical data

### Approvals

|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

### Downloads

|                    |                                                                                |
|--------------------|--------------------------------------------------------------------------------|
| Engineering Data   | <a href="#">CAD data – STEP</a>                                                |
| User Documentation | <a href="#">StorageConditionsTerminalBlocks</a><br><a href="#">Instruction</a> |
| Catalogues         | <a href="#">Catalogues in PDF-format</a>                                       |
| Brochures          |                                                                                |