


**ZDU 4-2/2AN****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Product image**

To feed through power, signal, and data is the classical requirement in electrical engineering and panel building. The insulating material, the connection system and the design of the terminal blocks are the differentiating features. A feed-through terminal block is suitable for joining and/or connecting one or more conductors. They could have one or more connection levels that are on the same potential or insulated against one another.

**General ordering data**

|            |                                                                                              |
|------------|----------------------------------------------------------------------------------------------|
| Version    | Feed-through terminal, Tension-clamp connection, 4 mm <sup>2</sup> , 800 V, 32 A, dark beige |
| Order No.  | <a href="#">1770370000</a>                                                                   |
| Type       | ZDU 4-2/2AN                                                                                  |
| GTIN (EAN) | 4032248143177                                                                                |
| Qty.       | 50 pc(s).                                                                                    |

**ZDU 4-2/2AN****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Technical data****Dimensions and weights**

|                          |            |                |            |
|--------------------------|------------|----------------|------------|
| Depth                    | 45.5 mm    | Depth (inches) | 1.791 inch |
| Depth including DIN rail | 46 mm      | Height         | 61.5 mm    |
| Height (inches)          | 2.421 inch | Width          | 6.1 mm     |
| Width (inches)           | 0.24 inch  | Net weight     | 8.909 g    |

**Temperatures**

|                                  |                |                                  |               |
|----------------------------------|----------------|----------------------------------|---------------|
| Storage temperature              | -25 °C...55 °C | Ambient temperature              | -5 °C...40 °C |
| Continuous operating temp., min. | -50 °C         | Continuous operating temp., max. | 120 °C        |

**Material data**

|                           |       |        |            |
|---------------------------|-------|--------|------------|
| Material                  | Wemid | Colour | dark beige |
| UL 94 flammability rating | V-0   |        |            |

**Rating data IECEx/ATEX**

|                                |                   |                                 |                   |
|--------------------------------|-------------------|---------------------------------|-------------------|
| Certificate No. (ATEX)         | DEMKO16ATEX1808U  | Certificate No. (IECEX)         | IECEXULD16.0036U  |
| Max. voltage (ATEX)            | 440 V             | Current (ATEX)                  | 29 A              |
| Wire cross section max. (ATEX) | 6 mm <sup>2</sup> | Max. voltage (IECEX)            | 440 V             |
| Current (IECEX)                | 29 A              | Wire cross section max. (IECEX) | 6 mm <sup>2</sup> |
| Marking EN 60079-7             | Ex eb II C Gb     | Ex 2014/34/EU label             | II 2 G D          |

**System specifications**

|                                     |                                                                                        |                               |     |
|-------------------------------------|----------------------------------------------------------------------------------------|-------------------------------|-----|
| Version                             | Tension-clamp connection,<br>for plug-in cross-connector,<br>One end without connector | End cover plate required      | Yes |
| Number of potentials                | 1                                                                                      | Number of levels              | 1   |
| Number of clamping points per level | 2                                                                                      | Number of potentials per tier | 1   |
| Levels cross-connected internally   | No                                                                                     | PE connection                 | No  |
| Rail                                | TS 35                                                                                  |                               |     |

**Additional technical data**

|                          |       |                             |         |
|--------------------------|-------|-----------------------------|---------|
| Explosion-tested version | Yes   | Number of similar terminals | 1       |
| Open sides               | right | Type of mounting            | Snap-on |

**CSA rating data**

|                               |                |                               |        |
|-------------------------------|----------------|-------------------------------|--------|
| Certificate No. (CSA)         | 200039-1152892 | Current size B (CSA)          | 35 A   |
| Current size C (CSA)          | 35 A           | Current size D (CSA)          | 5 A    |
| Voltage size B (CSA)          | 600 V          | Voltage size C (CSA)          | 600 V  |
| Voltage size D (CSA)          | 600 V          | Wire cross section max. (CSA) | 10 AWG |
| Wire cross section min. (CSA) | 26 AWG         |                               |        |

**Conductors for clamping (additional connection)**

Connection type, additional connection Tension-clamp connection

**Conductors for clamping (rated connection)**

|                      |                   |
|----------------------|-------------------|
| Blade size           | 0.6 x 3.5 mm      |
| Clamping range, max. | 6 mm <sup>2</sup> |

Creation date May 16, 2025 1:02:36 AM CEST

**ZDU 4-2/2AN****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Technical data**

|                                                                     |                                        |         |                      |
|---------------------------------------------------------------------|----------------------------------------|---------|----------------------|
| Clamping range, min.                                                | 0.13 mm <sup>2</sup>                   |         |                      |
| Connection cross-section, stranded, max.                            | 4 mm <sup>2</sup>                      |         |                      |
| Connection cross-section, stranded, min.                            | 0.5 mm <sup>2</sup>                    |         |                      |
| Connection direction                                                | Inclined / angled                      |         |                      |
| Gauge to IEC 60947-1                                                | A3                                     |         |                      |
| Number of connections                                               | 2                                      |         |                      |
| Stripping length                                                    | 10 mm                                  |         |                      |
| Tube length for twin wire-end ferrule                               | Tube length                            | min.    | 8 mm                 |
|                                                                     |                                        | max.    | 12 mm                |
|                                                                     | Cross-section for conductor connection | nominal | 0.5 mm <sup>2</sup>  |
|                                                                     | Tube length                            | min.    | 8 mm                 |
| Tube length for wire-end ferrule with plastic collar DIN 46228/4    |                                        | max.    | 12 mm                |
|                                                                     | Cross-section for conductor connection | nominal | 0.75 mm <sup>2</sup> |
|                                                                     | Tube length                            | min.    | 8 mm                 |
|                                                                     |                                        | max.    | 10 mm                |
|                                                                     | Cross-section for conductor connection | nominal | 0.5 mm <sup>2</sup>  |
|                                                                     | Tube length                            | min.    | 6 mm                 |
|                                                                     |                                        | max.    | 12 mm                |
|                                                                     | Cross-section for conductor connection | nominal | 0.75 mm <sup>2</sup> |
|                                                                     | Tube length                            | min.    | 6 mm                 |
|                                                                     |                                        | max.    | 12 mm                |
|                                                                     | Cross-section for conductor connection | nominal | 1 mm <sup>2</sup>    |
|                                                                     | Tube length                            | min.    | 8 mm                 |
|                                                                     |                                        | max.    | 12 mm                |
|                                                                     | Cross-section for conductor connection | nominal | 1.5 mm <sup>2</sup>  |
|                                                                     | Tube length                            | min.    | 8 mm                 |
|                                                                     |                                        | max.    | 12 mm                |
|                                                                     | Cross-section for conductor connection | nominal | 2.5 mm <sup>2</sup>  |
|                                                                     | Tube length                            | min.    | 10 mm                |
|                                                                     |                                        | max.    | 12 mm                |
|                                                                     | Cross-section for conductor connection | nominal | 4 mm <sup>2</sup>    |
| Tube length for wire-end ferrule without plastic collar DIN 46228/1 | Tube length                            | nominal | 10 mm                |
|                                                                     | Cross-section for conductor connection | nominal | 0.5 mm <sup>2</sup>  |
|                                                                     | Tube length                            | nominal | 10 mm                |
|                                                                     | Cross-section for conductor connection | nominal | 0.75 mm <sup>2</sup> |
|                                                                     | Tube length                            | nominal | 10 mm                |
|                                                                     | Cross-section for conductor connection | nominal | 1 mm <sup>2</sup>    |
|                                                                     | Tube length                            | min.    | 10 mm                |
|                                                                     |                                        | max.    | 12 mm                |
|                                                                     | Cross-section for conductor connection | nominal | 1.5 mm <sup>2</sup>  |
|                                                                     | Tube length                            | min.    | 10 mm                |
|                                                                     |                                        | max.    | 12 mm                |
|                                                                     | Cross-section for conductor connection | nominal | 2.5 mm <sup>2</sup>  |
|                                                                     | Tube length                            | nominal | 12 mm                |
|                                                                     | Cross-section for conductor connection | nominal | 4 mm <sup>2</sup>    |
| Twin wire-end ferrules, max.                                        | 1.5 mm <sup>2</sup>                    |         |                      |
| Twin wire-end ferrules, min.                                        | 0.5 mm <sup>2</sup>                    |         |                      |
| Type of connection                                                  | Tension-clamp connection               |         |                      |
| Wire connection cross section AWG, max.                             | AWG 10                                 |         |                      |
| Wire connection cross section AWG, min.                             | AWG 26                                 |         |                      |
| Wire connection cross section, finely stranded, max.                | 4 mm <sup>2</sup>                      |         |                      |
| Wire connection cross section, finely stranded, min.                | 0.5 mm <sup>2</sup>                    |         |                      |

**ZDU 4-2/2AN****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Technical data**

|                                                                                         |                   |
|-----------------------------------------------------------------------------------------|-------------------|
| Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/1, max. | 4 mm <sup>2</sup> |
|-----------------------------------------------------------------------------------------|-------------------|

|                                                                                         |                     |
|-----------------------------------------------------------------------------------------|---------------------|
| Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/1, min. | 0.5 mm <sup>2</sup> |
|-----------------------------------------------------------------------------------------|---------------------|

|                                                                                         |                   |
|-----------------------------------------------------------------------------------------|-------------------|
| Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/4, max. | 4 mm <sup>2</sup> |
|-----------------------------------------------------------------------------------------|-------------------|

|                                                                                         |                     |
|-----------------------------------------------------------------------------------------|---------------------|
| Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/4, min. | 0.5 mm <sup>2</sup> |
|-----------------------------------------------------------------------------------------|---------------------|

|                                                 |                   |
|-------------------------------------------------|-------------------|
| Wire connection cross-section, solid core, max. | 6 mm <sup>2</sup> |
|-------------------------------------------------|-------------------|

|                                                 |                     |
|-------------------------------------------------|---------------------|
| Wire connection cross-section, solid core, min. | 0.5 mm <sup>2</sup> |
|-------------------------------------------------|---------------------|

**Dimensions**

|              |         |
|--------------|---------|
| TS 35 offset | 50.5 mm |
|--------------|---------|

**General**

|                                         |        |                                         |               |
|-----------------------------------------|--------|-----------------------------------------|---------------|
| Rail                                    | TS 35  | Standards                               | IEC 60947-7-1 |
| Wire connection cross section AWG, max. | AWG 10 | Wire connection cross section AWG, min. | AWG 26        |

**Rating data**

|                                              |                   |                                 |               |
|----------------------------------------------|-------------------|---------------------------------|---------------|
| Rated cross-section                          | 4 mm <sup>2</sup> | Rated voltage                   | 800 V         |
| Rated DC voltage                             | 800 V             | Rated current                   | 32 A          |
| Current at maximum wires                     | 32 A              | Standards                       | IEC 60947-7-1 |
| Volume resistance according to IEC 60947-7-x | 1 mΩ              | Rated impulse withstand voltage | 8 kV          |
| Power loss in accordance with IEC 60947-7-x  | 1.02 W            | Pollution severity              | 3             |

**UL rating data**

|                                         |        |                                         |        |
|-----------------------------------------|--------|-----------------------------------------|--------|
| Certificate No. (UR)                    | E60693 | Conductor size Factory wiring max. (UR) | 10 AWG |
| Conductor size Factory wiring min. (UR) | 26 AWG | Conductor size Field wiring max. (UR)   | 10 AWG |
| Conductor size Field wiring min. (UR)   | 26 AWG | Current size C (UR)                     | 33 A   |
| Voltage size C (UR)                     | 600 V  |                                         |        |

**Classifications**

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC000897    | ETIM 7.0    | EC000897    |
| ETIM 8.0    | EC000897    | ETIM 9.0    | EC000897    |
| ETIM 10.0   | EC000897    | ECLASS 9.0  | 27-14-11-20 |
| ECLASS 9.1  | 27-14-11-20 | ECLASS 10.0 | 27-14-11-20 |
| ECLASS 11.0 | 27-14-11-20 | ECLASS 12.0 | 27-14-11-20 |
| ECLASS 13.0 | 27-25-01-01 | ECLASS 14.0 | 27-25-01-01 |
| ECLASS 15.0 | 27-25-01-01 |             |             |

**Environmental Product Compliance**

|                        |                             |
|------------------------|-----------------------------|
| RoHS Compliance Status | Compliant without exemption |
| REACH SVHC             | No SVHC above 0.1 wt%       |

## ZDU 4-2/2AN

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Approvals

Approvals



|                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
|-----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Approvals MAMID       | <a href="https://mdcop.weidmueller.com/mediadelivery/rendition/900_319217/-T1z1mm-S800/">https://mdcop.weidmueller.com/mediadelivery/rendition/900_319217/-T1z1mm-S800/</a> <a href="https://mdcop.weidmueller.com/mediadelivery/rendition/900_319222/-T1z1mm-S800/">https://mdcop.weidmueller.com/mediadelivery/rendition/900_319222/-T1z1mm-S800/</a> <a href="https://mdcop.weidmueller.com/mediadelivery/rendition/900_319226/-T1z1mm-S800/">https://mdcop.weidmueller.com/mediadelivery/rendition/900_319226/-T1z1mm-S800/</a> <a href="https://mdcop.weidmueller.com/mediadelivery/rendition/900_319213/-T1z1mm-S800/">https://mdcop.weidmueller.com/mediadelivery/rendition/900_319213/-T1z1mm-S800/</a> <a href="https://mdcop.weidmueller.com/mediadelivery/rendition/900_319234/-T1z1mm-S800/">https://mdcop.weidmueller.com/mediadelivery/rendition/900_319234/-T1z1mm-S800/</a> <a href="https://mdcop.weidmueller.com/mediadelivery/rendition/900_319240/-T1z1mm-S800/">https://mdcop.weidmueller.com/mediadelivery/rendition/900_319240/-T1z1mm-S800/</a> <a href="https://mdcop.weidmueller.com/mediadelivery/rendition/900_319255/-T1z1mm-S800/">https://mdcop.weidmueller.com/mediadelivery/rendition/900_319255/-T1z1mm-S800/</a> <a href="https://mdcop.weidmueller.com/mediadelivery/rendition/900_319260/-T1z1mm-S800/">https://mdcop.weidmueller.com/mediadelivery/rendition/900_319260/-T1z1mm-S800/</a> <a href="https://mdcop.weidmueller.com/mediadelivery/rendition/900_319262/-T1z1mm-S800/">https://mdcop.weidmueller.com/mediadelivery/rendition/900_319262/-T1z1mm-S800/</a> |
| ROHS                  | Conform                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| UL File Number Search | UL Website                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Certificate No. (UR)  | E60693                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |

## Downloads

|                                             |                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
|---------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Approval/Certificate/Document of Conformity | <a href="#">Attestation of Conformity</a><br><a href="#">UKCA Ex Attestation of Conformity</a><br><a href="#">ATEX Certificate</a><br><a href="#">IECEx Certificate</a><br><a href="#">CCC Ex Certificate</a><br><a href="#">UKCA Ex Certificate</a><br><a href="#">DNV Certificate</a><br><a href="#">Declaration of Conformity</a><br><a href="#">UKCA declaration of conformity</a><br><a href="#">Confirmation of Standards EN 45545-2 2020-10</a> |
| Engineering Data                            | <a href="#">CAD data – STEP</a>                                                                                                                                                                                                                                                                                                                                                                                                                        |
| User Documentation                          | <a href="#">NTI ZDU/ZPE 4-2/2AN</a><br><a href="#">StorageConditionsTerminalBlocks</a>                                                                                                                                                                                                                                                                                                                                                                 |
| Catalogues                                  | <a href="#">Catalogues in PDF-format</a>                                                                                                                                                                                                                                                                                                                                                                                                               |
| Brochures                                   |                                                                                                                                                                                                                                                                                                                                                                                                                                                        |

### ZDU 4-2/2AN

**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Drawings

