

**Cabtite (cable entry system)  
CABTITE FR 24/10 BK SET**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com



The frame, fabricated from a single piece, is quick and easy to assemble and consists of dimensionally stable, fibre-glass reinforced plastic. The captive foamed seal guarantees effective IP66 sealing in accordance with DIN EN 60529, even on painted and rough surfaces.

**General ordering data**

Type	CABTITE FR 24/10 BK SET
Order No.	<a href="#">2583720000</a>
Version	Frame, Cabtite (cable entry system), Polyamide, glass fibre-reinforced, Deep black, Height: 70 mm, Width: 153 mm, Depth: 19.6 mm, -40 °C... 120 °C, IP54, IP65, IP66
GTIN (EAN)	4050118617252
Qty.	1 pc(s).

**Cabtite (cable entry system)  
CABTITE FR 24/10 BK SET**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com

**Technical data**
**Dimensions and weights**

Width	153 mm	Width (inches)	6.024 inch
Height	70 mm	Height (inches)	2.756 inch
Height of lowest version	19.6 mm	Depth	19.6 mm
Depth (inches)	0.772 inch	Mounting dimension - width	32 mm
Mounting dimension - height	130 mm	Net weight	110 g
Diameter	5.5 mm		

**General information**

Tightening torque	3 Nm	Opening width	46 mm
Opening length	113.5 mm	UL 94 flammability rating	V-0
Sealing element	2 large sealing elements and 4 small sealing elements or 1 large sealing element and 6 small sealing elements or 10 small sealing elements	Halogen	No
Silicone	No	Sealing	TPE
Material	Polyamide, glass fibre-reinforced		

**Classifications**

ETIM 6.0	EC002624	ETIM 7.0	EC002624
eClass 9.0	27-18-28-15	eClass 9.1	27-18-92-65
eClass 10.0	27-18-28-15		

**Approvals**

ROHS	Conform
------	---------

**Downloads**

Engineering Data	<a href="#">STEP</a>
User Documentation	<a href="#">Cabtite Installation Instructions</a>

**Cabtite (cable entry system)  
CABTITE FR 24/10 BK SET**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com

**Drawings**

