

MB M3/M5 CRM**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Product image**

Mounting feet are used to mount components that cannot be snapped directly on a DIN rail.

General ordering data

Version	Sliding nut, M 5
Order No.	0503500000
Type	MB M3/M5 CRM
GTIN (EAN)	4008190182083
Qty.	20 pc(s).

MB M3/M5 CRM

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Depth	14 mm	Depth (inches)	0.551 inch
Height	25 mm	Height (inches)	0.984 inch
Width	12 mm	Width (inches)	0.472 inch
Net weight	3.55 g		

Temperatures

Ambient temperature	-5 °C...40 °C	Continuous operating temp., min.	-50 °C
Continuous operating temp., max.	100 °C		

Material data

Material	Polyamide 66	Surface finish	untreated
Colour	Cream	UL 94 flammability rating	V-2

System specifications

Version	For the mounting rails	Rail	TS 32
---------	------------------------	------	-------

Additional technical data

Explosion-tested version	No	Type of fixing	Snap-on
--------------------------	----	----------------	---------

Dimensions

Internal thread	M 5	Pitch in mm (P)	12 mm
-----------------	-----	-----------------	-------

General

Rail	TS 32	Surface finish	untreated
------	-------	----------------	-----------

Classifications

ETIM 6.0	EC000096	ETIM 7.0	EC000096
ETIM 8.0	EC000096	ETIM 9.0	EC000096
ETIM 10.0	EC000096	ECLASS 9.0	23-11-08-04
ECLASS 9.1	23-11-08-04	ECLASS 10.0	23-11-08-04
ECLASS 11.0	23-11-07-16	ECLASS 12.0	23-11-07-16
ECLASS 13.0	23-11-07-16	ECLASS 14.0	23-11-07-16
ECLASS 15.0	23-11-07-16		

Environmental Product Compliance

RoHS Compliance Status	Compliant
REACH SVHC	No SVHC above 0.1 wt%

Approvals

ROHS	Conform
------	---------

Downloads

User Documentation	StorageConditionsTerminalBlocks
Brochures	CAT 1 TERM 16/17 EN

Creation date May 15, 2025 12:49:52 PM CEST

MB M3/M5 CRM

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Drawings

