


**SAK 35N/35/IK****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Product image**

To feed through power, signal, and data is the classical requirement in electrical engineering and panel building. The insulating material, the connection system and the design of the terminal blocks are the differentiating features. A feed-through terminal block is suitable for joining and/or connecting one or more conductors. They could have one or more connection levels that are on the same potential or insulated against one another.

**General ordering data**

|                     |                                                                                                                            |
|---------------------|----------------------------------------------------------------------------------------------------------------------------|
| Version             | Feed-through terminal block, Screw connection, beige / yellow, 35 mm <sup>2</sup> , 125 A, 800 V, Number of connections: 2 |
| Order No.           | <a href="#">0608360000</a>                                                                                                 |
| Type                | SAK 35N/35/IK                                                                                                              |
| GTIN (EAN)          | 4008190090197                                                                                                              |
| Qty.                | 20 pc(s).                                                                                                                  |
| Alternative product | <a href="#">1020600000</a>                                                                                                 |

## SAK 35N/35/IK

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Dimensions and weights

|            |          |                 |            |
|------------|----------|-----------------|------------|
| Depth      | 60 mm    | Depth (inches)  | 2.362 inch |
| Height     | 58 mm    | Height (inches) | 2.283 inch |
| Width      | 16 mm    | Width (inches)  | 0.63 inch  |
| Net weight | 46.552 g |                 |            |

## Temperatures

|                                  |                |                                  |               |
|----------------------------------|----------------|----------------------------------|---------------|
| Storage temperature              | -25 °C...55 °C | Ambient temperature              | -5 °C...40 °C |
| Continuous operating temp., min. | -50 °C         | Continuous operating temp., max. | 100 °C        |

## Material data

|                           |       |        |                |
|---------------------------|-------|--------|----------------|
| Material                  | PA 66 | Colour | beige / yellow |
| UL 94 flammability rating | V-2   |        |                |

## System specifications

|                                     |                                                                             |                               |     |
|-------------------------------------|-----------------------------------------------------------------------------|-------------------------------|-----|
| Version                             | Screw connection, for screwable cross-connection, One end without connector | End cover plate required      | Yes |
| Number of potentials                | 1                                                                           | Number of levels              | 1   |
| Number of clamping points per level | 2                                                                           | Number of potentials per tier | 1   |
| Levels cross-connected internally   | No                                                                          | PE connection                 | No  |
| Rail                                | TS 35                                                                       | N-function                    | No  |
| PE function                         | No                                                                          | PEN function                  | No  |

## Additional technical data

|                          |       |                             |         |
|--------------------------|-------|-----------------------------|---------|
| Explosion-tested version | No    | Number of similar terminals | 1       |
| Open sides               | right | Type of mounting            | Clamped |

## CSA rating data

|                               |           |                               |       |
|-------------------------------|-----------|-------------------------------|-------|
| Certificate No. (CSA)         | 12400-201 | Current size C (CSA)          | 120 A |
| Voltage size C (CSA)          | 600 V     | Wire cross section max. (CSA) | 2 AWG |
| Wire cross section min. (CSA) | 12 AWG    |                               |       |

## Conductors for clamping (additional connection)

|                                                                                             |                    |                                        |                  |
|---------------------------------------------------------------------------------------------|--------------------|----------------------------------------|------------------|
| Conductor cross-section, flexible plus plastic collar DIN 46228/1, further connection, max. | 35 mm <sup>2</sup> | Connection type, additional connection | Screw connection |
|---------------------------------------------------------------------------------------------|--------------------|----------------------------------------|------------------|

## SAK 35N/35/IK

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Conductors for clamping (rated connection)

|                                                                                         |                     |                                                                                         |                     |
|-----------------------------------------------------------------------------------------|---------------------|-----------------------------------------------------------------------------------------|---------------------|
| Blade size                                                                              | S4 (DIN 6911)       | Clamping range, max.                                                                    | 50 mm <sup>2</sup>  |
| Clamping range, min.                                                                    | 2.5 mm <sup>2</sup> | Clamping screw                                                                          | M 6                 |
| Connection cross-section, stranded, max.                                                | 50 mm <sup>2</sup>  | Connection cross-section, stranded, min.                                                | 4 mm <sup>2</sup>   |
| Connection direction                                                                    | on side             | Gauge to IEC 60947-1                                                                    | B8                  |
| Number of connections                                                                   | 2                   | Stripping length                                                                        | 18 mm               |
| Tightening torque, max.                                                                 | 6 Nm                | Tightening torque, min.                                                                 | 4 Nm                |
| Twin wire-end ferrules, max.                                                            | 16 mm <sup>2</sup>  | Twin wire-end ferrules, min.                                                            | 1.5 mm <sup>2</sup> |
| Type of connection                                                                      | Screw connection    | Wire connection cross section AWG, max.                                                 | AWG 2               |
| Wire connection cross section AWG, min.                                                 | AWG 12              | Wire connection cross section, finely stranded, max.                                    | 35 mm <sup>2</sup>  |
| Wire connection cross section, finely stranded, min.                                    | 2.5 mm <sup>2</sup> | Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/1, max. | 35 mm <sup>2</sup>  |
| Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/1, min. | 1.5 mm <sup>2</sup> | Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/4, max. | 35 mm <sup>2</sup>  |
| Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/4, min. | 2.5 mm <sup>2</sup> | Wire connection cross-section, solid core, max.                                         | 16 mm <sup>2</sup>  |
| Wire connection cross-section, solid core, min.                                         | 2.5 mm <sup>2</sup> |                                                                                         |                     |

## General

|                                         |       |                                         |               |
|-----------------------------------------|-------|-----------------------------------------|---------------|
| Rail                                    | TS 35 | Standards                               | IEC 60947-7-1 |
| Wire connection cross section AWG, max. | AWG 2 | Wire connection cross section AWG, min. | AWG 12        |

## Rating data

|                                              |                    |                                 |               |
|----------------------------------------------|--------------------|---------------------------------|---------------|
| Rated cross-section                          | 35 mm <sup>2</sup> | Rated voltage                   | 800 V         |
| Rated DC voltage                             | 800 V              | Rated current                   | 125 A         |
| Current at maximum wires                     | 150 A              | Standards                       | IEC 60947-7-1 |
| Volume resistance according to IEC 60947-7-x | 0.26 mΩ            | Rated impulse withstand voltage | 8 kV          |
| Power loss in accordance with IEC 60947-7-x  | 4 W                | Pollution severity              | 3             |

## UL rating data

|                                         |        |                                         |       |
|-----------------------------------------|--------|-----------------------------------------|-------|
| Certificate No. (UR)                    | E60693 | Conductor size Factory wiring max. (UR) | 2 AWG |
| Conductor size Factory wiring min. (UR) | 12 AWG | Conductor size Field wiring max. (UR)   | 2 AWG |
| Conductor size Field wiring min. (UR)   | 12 AWG | Current size C (UR)                     | 100 A |
| Voltage size C (UR)                     | 600 V  |                                         |       |

## Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC000897    | ETIM 7.0    | EC000897    |
| ETIM 8.0    | EC000897    | ETIM 9.0    | EC000897    |
| ETIM 10.0   | EC000897    | ECLASS 9.0  | 27-14-11-20 |
| ECLASS 9.1  | 27-14-11-20 | ECLASS 10.0 | 27-14-11-20 |
| ECLASS 11.0 | 27-14-11-20 | ECLASS 12.0 | 27-14-11-20 |
| ECLASS 13.0 | 27-25-01-01 | ECLASS 14.0 | 27-25-01-01 |
| ECLASS 15.0 | 27-25-01-01 |             |             |

## SAK 35N/35/IK

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Environmental Product Compliance

|                        |                             |
|------------------------|-----------------------------|
| RoHS Compliance Status | Compliant without exemption |
| REACH SVHC             | No SVHC above 0.1 wt%       |

## Approvals

Approvals



|                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
|-----------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Approvals MAMID | <a href="https://mdcop.weidmueller.com/mediadelivery/rendition/900_319222/-T1z1mm-S800/">https://mdcop.weidmueller.com/mediadelivery/rendition/900_319222/-T1z1mm-S800/</a> <a href="https://mdcop.weidmueller.com/mediadelivery/rendition/900_319226/-T1z1mm-S800/">https://mdcop.weidmueller.com/mediadelivery/rendition/900_319226/-T1z1mm-S800/</a> <a href="https://mdcop.weidmueller.com/mediadelivery/rendition/900_319234/-T1z1mm-S800/">https://mdcop.weidmueller.com/mediadelivery/rendition/900_319234/-T1z1mm-S800/</a> <a href="https://mdcop.weidmueller.com/mediadelivery/rendition/900_319262/-T1z1mm-S800/">https://mdcop.weidmueller.com/mediadelivery/rendition/900_319262/-T1z1mm-S800/</a> <a href="https://mdcop.weidmueller.com/mediadelivery/rendition/900_319260/-T1z1mm-S800/">https://mdcop.weidmueller.com/mediadelivery/rendition/900_319260/-T1z1mm-S800/</a> |
|-----------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

|                       |            |
|-----------------------|------------|
| ROHS                  | Conform    |
| UL File Number Search | UL Website |
| Certificate No. (UR)  | E60693     |

## Downloads

|                                             |                                                                                                                                |
|---------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------|
| Approval/Certificate/Document of Conformity | <a href="#">DNV Certificate</a><br><a href="#">Declaration of Conformity</a><br><a href="#">UKCA declaration of conformity</a> |
| Engineering Data                            | <a href="#">CAD data – STEP</a>                                                                                                |
| Product Change Notification                 | <a href="#">20210308 Technical Change SAK PA 35</a>                                                                            |
| User Documentation                          | <a href="#">StorageConditionsTerminalBlocks</a>                                                                                |
| Catalogues                                  | <a href="#">Catalogues in PDF-format</a>                                                                                       |