

Catalog Number: XQM0606
Product ID: 7TCA297020R0493
EAN Number: 05011949209589
Status: Active

Liquid Tight Fitting for Covered Conduit, Straight with External Male Thread, Conduit Size 32mm, M32 Thread, Very High Mechanical and UV Protection, IP66, IP67 Ratings, Nickel Plated Brass with a Co-Polyester Seal and Nylon Insert

North American Specifications (UNSPSC)

UNSPSC	39121420 Liquid tight connectors
IGCC	4585 Liquid tight connectors
Brand Name	Kopex
Type	Straight Fitting with External Thread for Covered Conduit
Special Features	Very High UV Protection and Mechanical Protection
Application	For Insertion Into Threaded Entries & Knock-outs Using a Locknut to Secure
Standard	UL E60625, BSI Kitemark KM-90009, Low Voltage Directive
Size	Conduit Size 32mm
Connection	M32 Thread
Material	Brass with a Co-Polyester Seal and Nylon Insert
Finish	Nickel Plated
Color	Metallic
Insulation	IP66, 67 Rating
Temperature Rating	Static: -65 to 150 Degrees C, Dynamic: -45 to 150 Degrees C

European Specifications (ETIM)

ETIM	EC001180 Screw connection for protective metallic hose
Nominal diameter	32mm
Nominal size in inch	1 inch
Degree of protection (IP) conduit dependant	IP66-IP67
Model	Straight
Revolving thread	N
Construction type	External thread
Thread type	Metric
Thread connection size	M32 x 1.5
One-piece	Y
Material housing	Brass
Surface protection	Nickel-plated
Thread length	15mm
Total length	42mm
Total height	42mm
Approved in combination with protective conduit DIN EN 61386-23	N
Approved in combination with protective conduit CSA	N
Approved in combination with protective conduit UL	Y
Approved in combination with protective conduit FI	N
Operating temperature	-65-+150°C

Packaging

Outer Quantity	5
Outer Dimensions (inches)	1x1x1
Weight Uom	0.31 lbs. Each

For further technical assistance, please contact us...

Thomas & Betts - USA
860 Ridge Lake Blvd.
Memphis, TN 38120
www.tnb.com

T&B Technical Support
MS 3B-50
860 Ridge Lake Blvd.
Memphis, TN 38120

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com