

Technical data sheet

Flexible Control and Tray Cable TRAY-ER PVC · Unshielded

LUTZE SILFLEX® N Control Cable PVC For Stationary Applications



Identification

Type SI N PVC TRAY-ER 4×AWG2 SW
Part No. [A3220204](#)

Product version

Datasheet version 00

Use/Application/Properties

- Application
- Machine tools, machine and plant construction, VAC technology as well as other uses.
 - Compliant with NFPA 79 requirements
 - TC-ER-JP for use with cable trays without conduit, which can reduce installation costs in industrial environments
 - WTTC – wind turbine tray cable rating for use in wind power generation
 - Dry, damp or wet locations
- Properties
- Crush impact resistant
 - Gas/vapor-tight sheath per UL 1277
 - Non-wicking fillers
 - Ecolab certified resistance to common cleaning agents and chemicals used in food and beverage washdown procedures
 - Sunlight resistant
 - Flame retardant
 - "direct burial" for installation in the ground
 - Talc free and silicone free

Construction

Description SILFLEX® CONTROL CABLE PVC
Number of conductors/cross-section 4×AWG2
Number of conductors 4
Cross-section, metric 35 mm²
Cross-section AWG AWG 2
Jacket material PVC

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU
Tel. +44 (0)1827 31333-0
www.lutze.com • sales.gb@lutze.co.uk

Germany: Friedrich Lütze GmbH

Postfach 12 24 (PLZ 71366) • Bruckwiesenstraße 17-19 • D-71384 Weinstadt
Tel. +49 (0)7151 6053-0
www.luetze.de • info@luetze.de

18.09.2024 • Subject to technical modification

Part No. [A3220204](#) • Datasheet version: 00

page 1 of 3



SYSTEMATIC TECHNOLOGY

Technical data sheet

Flexible Control and Tray Cable TRAY-ER PVC · Unshielded

Jacket color	black similar to RAL 9005
Outer Ø	31 mm
Outer Ø	1.219 inch
Weight	183.6 kg/100 m
Weight	1234 Lbs/Mft
Cu-Index	130.1 kg/100 m
Cu-Index	874 Lbs/Mft

Construction Element 1

Element construction	AWG2/4C
Conductor construction	AWG 2 (665/30)
Conductor	AWG conductor CU-wire bare
Conductor category	Fine wire Class K
Conductor marking	black · with white number print · green/yellow
Conductor insulation	PVC/Nylon

Overall construction

Drain wire	CU-wire tin-plated
Overall shield	Foil shield Aluminium laminate Braid shield Tinned copper wires
Jacket characteristics	Oil resistant UV resistant (normal lighting conditions) Silicone free

Technical data

Rated voltage U_N	600 V 90C UL TC-ER-JP 1000 V WTTC 90C 600 V UL MTW 1000 V 105C AWM
Temperature range fixed	-40 °C ... +105 °C
Minimum bending radius fixed	6×D

Technical Data Element 1

Element construction	AWG2/4C
----------------------	---------

Technical data sheet

Flexible Control and Tray Cable TRAY-ER PVC · Unshielded

Certifications/Standards

Certifications	UL Type MTW or DP-1 Meets NEC 336, 392, 725, 727 Class I and II, Div. 2 and Class I Zone 2 per NEC 501, 502, 505 C(UL) TC and CIC FT4 UL 1277 TC-ER-JP WTTC
UL style	AWM 20886
Conformity	CE RoHS REACH TSCA
Oil resistant according to	Oil Res II

General

Note	CE These products are in conformity with the EU Low Voltage Directive 2014/35/EU
------	----------------------------------------------------------------------------------