

## Technical data sheet

Flexible Control and Tray Cable TRAY PVC · Unshielded

### LUTZE SILFLEX® N Control Cable PVC For Stationary Applications



#### Identification

Type SI N PVC TRAY 2×AWG14 SW  
Part No. [A3221402](#)

#### Product version

Datasheet version 00

#### Use/Application/Properties

- Application
- Machine tools, machine and plant construction, VAC technology as well as other uses.
  - Compliant with NFPA 79 requirements
  - TC for use with cable trays without conduit, which can reduce installation costs in industrial environments
  - WTTC – wind turbine tray cable rating for use in wind power generation
  - PLTC for installation in cable trays
  - ITC Instrumentation Tray Cable
  - Dry, damp or wet locations
- Properties
- Crush impact resistant
  - Gas/vapor-tight sheath per UL 1277
  - Non-wicking fillers
  - Ecolab certified resistance to common cleaning agents and chemicals used in food and beverage washdown procedures
  - Sunlight resistant
  - Flame retardant
  - "direct burial" for installation in the ground
  - Talc free and silicone free

#### Construction

Description SILFLEX® CONTROL CABLE PVC  
Number of conductors/cross-section 2×AWG14  
Number of conductors 2  
Cross-section, metric 2.5 mm<sup>2</sup>  
Cross-section AWG AWG 14

#### United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park  
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU  
Tel. +44 (0)1827 31333-0  
[www.lutze.com](http://www.lutze.com) • [sales.gb@lutze.co.uk](mailto:sales.gb@lutze.co.uk)

#### Germany: Friedrich Lütze GmbH

Postfach 12 24 (PLZ 71366) • Bruckwiesenstraße 17-19 • D-71384 Weinstadt  
Tel. +49 (0)7151 6053-0  
[www.luetze.de](http://www.luetze.de) • [info@luetze.de](mailto:info@luetze.de)

18.09.2024 • Subject to technical modification

Part No. [A3221402](#) • Datasheet version: 00

page 1 of 3



SYSTEMATIC TECHNOLOGY

## Technical data sheet

### Flexible Control and Tray Cable TRAY PVC · Unshielded

---

Jacket material	PVC
Jacket color	black similar to RAL 9005
Outer Ø	8.6 mm
Outer Ø	0.34 inch
Weight	9.2 kg/100 m
Weight	62 Lbs/Mft
Cu-Index	3.7 kg/100 m
Cu-Index	25 Lbs/Mft

---

#### Construction Element 1

---

Element construction	AWG14/2C
Conductor construction	AWG 14 (41/30)
Conductor	AWG conductor CU-wire bare
Conductor category	Fine wire Class K
Conductor marking	black • with white number print
Conductor insulation	PVC/Nylon

---

#### Overall construction

---

Jacket characteristics	Oil resistant UV resistant (normal lighting conditions) Silicone free
------------------------	---

---

#### Technical data

---

Rated voltage $U_N$	600 V 90C UL TC 1000 V WTTC 90C 600 V UL MTW 1000 V 105C AWM
Temperature range fixed	-40 °C ... +105 °C
Minimum bending radius fixed	4×D

---

#### Technical Data Element 1

---

Element construction	AWG14/2C
----------------------	----------

---

#### Certifications/Standards

---

Certifications	UL Type MTW or DP-1 Meets NEC 336, 392, 725, 727 Class I and II, Div. 2 and Class I Zone 2 per NEC 501, 502, 505 C(UL) TC and CIC FT4 UL 1277 TC WTTC PLTC ITC
UL style	AWM 20886

---

## Technical data sheet

### Flexible Control and Tray Cable TRAY PVC · Unshielded

---

Conformity	CE RoHS REACH TSCA
Oil resistant according to	Oil Res II

---

#### General

---

Note	CE These products are in conformity with the EU Low Voltage Directive 2014/35/EU
------	--